

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	01 Hour 59 Min 53 Sec
Total Counter :	456098	Total Running Time :	1553 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.07	kN	No		
HEP :	25.0 %	9.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.90	kN	Yes 15	Times	
Ref :		7.75	kN			
LCP :	2.0 %	7.59	kN	Yes 15	Times	
LEP :	25.0 %	5.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.58	kN	Min :	2.53	kN	Punch NO.;	16
SD :	0.40	%	Max :	2.61	kN	Punch NO.;	2
Mean Main Pressure :	7.74	kN	Min :	7.23	kN	Punch NO.;	16
SD :	2.60	%	Max :	8.18	kN	Punch NO.;	34
Filling Depth :	Increase ; 82	Times	Decrease ; 77	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	5.58	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.804	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	98	Min			
Lower Punch Remain Time (S2):	72	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.26	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	456098	Tablets			
A.W.C Counter :	421847	Tablets			
HEP :	1256 (0.3%)	Tablets	LEP :	349 (0.1%)	Tablets
GOOD :	420242 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	01 Hour 59 Min 53 Sec
Total Counter :	456098	Total Running Time :	1553 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	32	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.77	kN	No		
HEP :	25.0 %	9.39	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	7.67	kN	Yes	15 Times	
Ref :		7.52	kN			
LCP :	2.0 %	7.36	kN	Yes	15 Times	
LEP :	25.0 %	5.64	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	5.26	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.25	kN	Min :	2.22	kN	Punch NO.;	40
SD :	0.50	%	Max :	2.28	kN	Punch NO.;	6
Mean Main Pressure :	7.50	kN	Min :	6.78	kN	Punch NO.;	18
SD :	3.90	%	Max :	8.35	kN	Punch NO.;	76
Filling Depth :	Increase ;	143	Times	Decrease ;	130	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	1.76	mm
Filling Depth :	6.09	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	98	Min			
Lower Punch Remain Time (S2):	72	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.26	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	456098	Tablets			
A.W.C Counter :	421847	Tablets			
HEP :	1256 (0.3%)	Tablets	LEP :	349 (0.1%)	Tablets
GOOD :	420242 (99.6%)	Tablets			