

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	sp98936	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 21 Sec
Total Counter :	665804	Total Running Time :	1554 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.43	kN	No		
HEP :	25.0 %	10.03	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.18	kN	Yes 15	Times	
Ref :		8.02	kN			
LCP :	2.0 %	7.86	kN	Yes 15	Times	
LEP :	25.0 %	6.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.53	kN	Punch NO.;	11
SD :	0.50	%	Max :	2.59	kN	Punch NO.;	51
Mean Main Pressure :	7.49	kN	Min :	6.96	kN	Punch NO.;	19
SD :	3.60	%	Max :	8.10	kN	Punch NO.;	49
Filling Depth :	Increase ; 98	Times	Decrease ;	113	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	6.06	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.757	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	28
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.10	kN	Max Punch ;	36
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	665804	Tablets			
A.W.C Counter :	631366	Tablets			
HEP :	1256 (0.2%)	Tablets	LEP :	519 (0.1%)	Tablets
GOOD :	629591 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	sp98936	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 21 Sec
Total Counter :	665804	Total Running Time :	1554 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	32	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.88	kN	No		
HEP :	25.0 %	9.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.75	kN	Yes 15	Times	
Ref :		7.60	kN			
LCP :	2.0 %	7.45	kN	Yes 15	Times	
LEP :	25.0 %	5.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.32	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.18	kN	Punch NO.;	77
SD :	0.50	%	Max :	2.23	kN	Punch NO.;	3
Mean Main Pressure :	5.84	kN	Min :	4.57	kN	Punch NO.;	77
SD :	11.30	%	Max :	7.22	kN	Punch NO.;	45
Filling Depth :	Increase ;	171	Times	Decrease ;	141	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.80	mm	Pre Thickness ;	3.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	1.76	mm
Filling Depth :	6.18	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.757	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	28
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	17
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	665804	Tablets			
A.W.C Counter :	631366	Tablets			
HEP :	1256 (0.2%)	Tablets	LEP :	519 (0.1%)	Tablets
GOOD :	629591 (99.7%)	Tablets			