

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	pb97604	Batch NO. :	JLM2500550
Print Interval :	50000 Tablets	Running Time :	01 Hour 31 Min 43 Sec
Total Counter :	350302	Total Running Time :	1555 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	36	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.44	kN	No		
HEP :	25.0 %	11.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.97	kN	Yes 15	Times	
Ref :		8.80	kN			
LCP :	2.0 %	8.62	kN	Yes 15	Times	
LEP :	25.0 %	6.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.65	kN	Min :	2.63	kN	Punch NO.;	17
SD :	0.40	%	Max :	2.68	kN	Punch NO.;	51
Mean Main Pressure :	8.90	kN	Min :	8.30	kN	Punch NO.;	19
SD :	2.90	%	Max :	9.33	kN	Punch NO.;	51
Filling Depth :	Increase ;	147	Times	Decrease ;	159	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.58	mm	Main Thickness ;	1.59	mm
Filling Depth :	5.48	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	108	Min			
Lower Punch Remain Time (S2):	82	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	75

Tablet Data (N/A)

Total Counter :	350302	Tablets			
A.W.C Counter :	340652	Tablets			
HEP :	25 (0.0%)	Tablets	LEP :	70 (0.0%)	Tablets
GOOD :	340557 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	pb97604	Batch NO. :	JLM2500550
Print Interval :	50000 Tablets	Running Time :	01 Hour 31 Min 43 Sec
Total Counter :	350302	Total Running Time :	1555 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.61	kN	No		
HEP :	25.0 %	10.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.33	kN	Yes 15	Times	
Ref :		8.16	kN			
LCP :	2.0 %	8.00	kN	Yes 15	Times	
LEP :	25.0 %	6.12	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.33	kN	Min :	2.29	kN	Punch NO.;	61
SD :	0.60	%	Max :	2.36	kN	Punch NO.;	2
Mean Main Pressure :	8.18	kN	Min :	7.55	kN	Punch NO.;	19
SD :	4.00	%	Max :	9.26	kN	Punch NO.;	2
Filling Depth :	Increase ;	207	Times	Decrease ;	189	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.75	mm	Pre Thickness ;	3.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	5.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	108	Min			
Lower Punch Remain Time (S2):	82	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.24	kN	Max Punch ;	3
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	75

Tablet Data (N/A)

Total Counter :	350302	Tablets			
A.W.C Counter :	340652	Tablets			
HEP :	25 (0.0%)	Tablets	LEP :	70 (0.0%)	Tablets
GOOD :	340557 (100.0%)	Tablets			