

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500650
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 45 Sec
Total Counter :	29280	Total Running Time :	1557 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	35	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.44	kN	No		
HEP :	25.0 %	11.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.97	kN	Yes 15	Times	
Ref :		8.80	kN			
LCP :	2.0 %	8.62	kN	Yes 15	Times	
LEP :	25.0 %	6.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.64	kN	Min :	2.62	kN	Punch NO.;	24
SD :	0.30	%	Max :	2.67	kN	Punch NO.;	76
Mean Main Pressure :	8.64	kN	Min :	8.14	kN	Punch NO.;	19
SD :	2.70	%	Max :	9.60	kN	Punch NO.;	76
Filling Depth :	Increase ;	191	Times	Decrease ;	210	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	138600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	3	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.58	mm	Main Thickness ;	1.59	mm
Filling Depth :	5.85	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	132	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.21	kN	Max Punch ;	36
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	29280	Tablets			
A.W.C Counter :	27606	Tablets			
HEP :	236 (0.9%)	Tablets	LEP :	9 (0.0%)	Tablets
GOOD :	27361 (99.1%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500650
Print Interval :	50000 Tablets	Running Time :	00 Hour 12 Min 46 Sec
Total Counter :	29318	Total Running Time :	1557 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.61	kN	No		
HEP :	25.0 %	10.21	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.33	kN	Yes	15	Times
Ref :		8.16	kN			
LCP :	2.0 %	8.00	kN	Yes	15	Times
LEP :	25.0 %	6.12	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.32	kN	Min :	2.29	kN	Punch NO.;	65
SD :	0.50	%	Max :	2.35	kN	Punch NO.;	76
Mean Main Pressure :	8.09	kN	Min :	7.52	kN	Punch NO.;	7
SD :	4.80	%	Max :	10.34	kN	Punch NO.;	76
Filling Depth :	Increase ;	230	Times	Decrease ;	208	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	138600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	3	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.75	mm	Pre Thickness ;	3.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	6.19	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	132	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.21	kN	Max Punch ;	40
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	29318	Tablets			
A.W.C Counter :	27606	Tablets			
HEP :	236 (0.9%)	Tablets	LEP :	9 (0.0%)	Tablets
GOOD :	27361 (99.1%)	Tablets			