

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG STJL1A00
User ID :	sp98936	Batch NO. :	JLM2500650
Print Interval :	50000 Tablets	Running Time :	01 Hour 56 Min 32 Sec
Total Counter :	450302	Total Running Time :	1559 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.89	kN	No		
HEP :	25.0 %	11.43	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	9.33	kN	Yes	15 Times	
Ref :		9.14	kN			
LCP :	2.0 %	8.96	kN	Yes	15 Times	
LEP :	25.0 %	6.86	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	6.40	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.63	kN	Min :	2.60	kN	Punch NO.;	68
SD :	0.40	%	Max :	2.66	kN	Punch NO.;	2
Mean Main Pressure :	9.19	kN	Min :	8.48	kN	Punch NO.;	21
SD :	3.60	%	Max :	10.13	kN	Punch NO.;	6
Filling Depth :	Increase ;	242	Times	Decrease ;	275	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.58	mm	Main Thickness ;	1.59	mm
Filling Depth :	6.19	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	56	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.22	kN	Max Punch ;	21
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	450302	Tablets			
A.W.C Counter :	436947	Tablets			
HEP :	788 (0.2%)	Tablets	LEP :	583 (0.1%)	Tablets
GOOD :	435576 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG STJL1A00
User ID :	sp98936	Batch NO. :	JLM2500650
Print Interval :	50000 Tablets	Running Time :	01 Hour 56 Min 32 Sec
Total Counter :	450302	Total Running Time :	1559 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	24	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		700000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.31	kN	No		
HEP :	25.0 %	10.88	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.88	kN	Yes 15	Times	
Ref :		8.70	kN			
LCP :	2.0 %	8.53	kN	Yes 15	Times	
LEP :	25.0 %	6.53	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.09	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.30	kN	Min :	2.27	kN	Punch NO.;	77
SD :	0.50	%	Max :	2.33	kN	Punch NO.;	10
Mean Main Pressure :	8.69	kN	Min :	7.90	kN	Punch NO.;	9
SD :	3.70	%	Max :	9.34	kN	Punch NO.;	52
Filling Depth :	Increase ;	279	Times	Decrease ;	258	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.75	mm	Pre Thickness ;	3.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	6.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	56	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	21
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	450302	Tablets			
A.W.C Counter :	436947	Tablets			
HEP :	788 (0.2%)	Tablets	LEP :	583 (0.1%)	Tablets
GOOD :	435576 (99.7%)	Tablets			