

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	sj97904	Batch NO. :	JLM2500410
Print Interval :	50000 Tablets	Running Time :	02 Hour 49 Min 35 Sec
Total Counter :	623588	Total Running Time :	1563 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.03	kN	No		
HEP :	25.0 %	15.42	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	12.58	kN	Yes	15 Times	
Ref :		12.33	kN			
LCP :	2.0 %	12.09	kN	Yes	15 Times	
LEP :	25.0 %	9.25	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	8.63	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.94	kN	Min :	2.89	kN	Punch NO.;	13
SD :	0.60	%	Max :	3.02	kN	Punch NO.;	35
Mean Main Pressure :	12.02	kN	Min :	11.31	kN	Punch NO.;	16
SD :	3.10	%	Max :	13.67	kN	Punch NO.;	36
Filling Depth :	Increase ;	46	Times	Decrease ;	73	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.97	mm	Main Thickness ;	1.97	mm
Filling Depth :	7.19	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.29	kN	Max Punch ;	77
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	623588	Tablets			
A.W.C Counter :	606365	Tablets			
HEP :	221 (0.0%)	Tablets	LEP :	49 (0.0%)	Tablets
GOOD :	606095 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STJL1B00
User ID :	sj97904	Batch NO. :	JLM2500410
Print Interval :	50000 Tablets	Running Time :	02 Hour 49 Min 35 Sec
Total Counter :	623588	Total Running Time :	1563 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	16	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		650000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.92	kN	No		
HEP :	25.0 %	12.42	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.14	kN	Yes	15	Times
Ref :		9.94	kN			
LCP :	2.0 %	9.74	kN	Yes	15	Times
LEP :	25.0 %	7.45	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.73	kN	Min :	2.68	kN	Punch NO.;	20
SD :	0.80	%	Max :	2.84	kN	Punch NO.;	35
Mean Main Pressure :	9.69	kN	Min :	9.04	kN	Punch NO.;	16
SD :	4.10	%	Max :	11.67	kN	Punch NO.;	36
Filling Depth :	Increase ;	28	Times	Decrease ;	32	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.18	mm	Main Thickness ;	2.19	mm
Filling Depth :	7.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.808	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.29	kN	Max Punch ;	77
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	39
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	623588	Tablets			
A.W.C Counter :	606365	Tablets			
HEP :	221 (0.0%)	Tablets	LEP :	49 (0.0%)	Tablets
GOOD :	606095 (100.0%)	Tablets			