

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	pb97604	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	06 Hour 23 Min 29 Sec
Total Counter :	706320	Total Running Time :	1575 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	186	%	Manual ;	33	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1000000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.75	kN	No		
HEP :	20.0 %	17.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.71	kN	Yes 15	Times	
Ref :		14.43	kN			
LCP :	2.0 %	14.14	kN	Yes 15	Times	
LEP :	20.0 %	11.54	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.68	kN	Min :	1.49	kN	Punch NO.;	28
		5.30	%	Max :	1.83	kN	Punch NO.;	37
Mean Main Pressure :		14.46	kN	Min :	14.40	kN	Punch NO.;	2
	SD :	0.20	%	Max :	14.59	kN	Punch NO.;	24
Filling Depth :	Increase ;	0	Times	Decrease ;	1	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.42	mm	Main Thickness ;	1.42	mm
Filling Depth :	7.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.764	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.37	kN		
	Max ;	0.40	kN	Max Punch ;	43
Lower Punch :	Average ;	0.02	kN		
	Max ;	0.03	kN	Max Punch ;	3
Ejection Force :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	706320	Tablets			
A.W.C Counter :	697953	Tablets			
HEP :	130 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	697823 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG STIR1B00
User ID :	pb97604	Batch NO. :	IRM2507840
Print Interval :	50000 Tablets	Running Time :	06 Hour 23 Min 29 Sec
Total Counter :	706320	Total Running Time :	1575 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	176	%	Manual ;	16	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.73	kN	No		
HEP :	20.0 %	17.29	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.69	kN	Yes 15	Times	
Ref :		14.40	kN			
LCP :	2.0 %	14.12	kN	Yes 15	Times	
LEP :	20.0 %	11.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.08	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.82	kN	Min :	1.60	kN	Punch NO.;	17
SD :	5.60	%	Max :	2.12	kN	Punch NO.;	50
Mean Main Pressure :	14.39	kN	Min :	14.33	kN	Punch NO.;	48
SD :	0.10	%	Max :	14.46	kN	Punch NO.;	24
Filling Depth :	Increase ; 0	Times	Decrease ; 0	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.45	mm
Filling Depth :	7.64	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.764	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.37	kN		
	Max ;	0.40	kN	Max Punch ;	37
Lower Punch :	Average ;	0.02	kN		
	Max ;	0.03	kN	Max Punch ;	3
Ejection Force :	Average ;	0.16	kN		
	Max ;	0.20	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	706320	Tablets			
A.W.C Counter :	697953	Tablets			
HEP :	130 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	697823 (100.0%)	Tablets			