

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	01 Hour 05 Min 05 Sec
Total Counter :	250124	Total Running Time :	1578 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	18	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.20	kN	No		
HEP :	20.0 %	11.26	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.57	kN	Yes	15	Times
Ref :		9.38	kN			
LCP :	2.0 %	9.19	kN	Yes	15	Times
LEP :	20.0 %	7.51	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.38	kN	Min :	0.91	kN	Punch NO.;	65
SD :	11.00	%	Max :	1.69	kN	Punch NO.;	38
Mean Main Pressure :	8.94	kN	Min :	7.31	kN	Punch NO.;	65
SD :	5.90	%	Max :	10.18	kN	Punch NO.;	50
Filling Depth :	Increase ;	318	Times	Decrease ;	321	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.10	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.709	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.11	kN	Max Punch ;	46
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.16	kN		
	Max ;	0.34	kN	Max Punch ;	60

Tablet Data (N/A)

Total Counter :	250124	Tablets			
A.W.C Counter :	232324	Tablets			
HEP :	1017 (0.4%)	Tablets	LEP :	388 (0.2%)	Tablets
GOOD :	230919 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	01 Hour 05 Min 05 Sec
Total Counter :	250124	Total Running Time :	1578 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.84	kN	No		
HEP :	20.0 %	11.85	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.07	kN	Yes 15	Times	
Ref :		9.88	kN			
LCP :	2.0 %	9.68	kN	Yes 15	Times	
LEP :	20.0 %	7.90	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.61	kN	Min :	1.22	kN	Punch NO.;	49
SD :	10.30	%	Max :	1.94	kN	Punch NO.;	8
Mean Main Pressure :	10.16	kN	Min :	8.31	kN	Punch NO.;	49
SD :	6.80	%	Max :	11.44	kN	Punch NO.;	9
Filling Depth :	Increase ;	182	Times	Decrease ;	182	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.10	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.709	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	10
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.16	kN		
	Max ;	0.34	kN	Max Punch ;	60

Tablet Data (N/A)

Total Counter :	250124	Tablets			
A.W.C Counter :	232324	Tablets			
HEP :	1017 (0.4%)	Tablets	LEP :	388 (0.2%)	Tablets
GOOD :	230919 (99.4%)	Tablets			