

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	05 Hour 03 Min 38 Sec
Total Counter :	1050694	Total Running Time :	1582 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.41	kN	No		
HEP :	27.0 %	16.03	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.87	kN	Yes	15	Times
Ref :		12.62	kN			
LCP :	2.0 %	12.37	kN	Yes	15	Times
LEP :	27.0 %	9.21	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.83	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.09	kN	Min :	1.66	kN	Punch NO.;	11
		7.80	%	Max :	2.43	kN	Punch NO.;	40
Mean Main Pressure :		12.68	kN	Min :	10.23	kN	Punch NO.;	49
	SD :	6.20	%	Max :	13.97	kN	Punch NO.;	34
Filling Depth :	Increase ;	911	Times	Decrease ;	883	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.11	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.667	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	9
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.14	kN		
	Max ;	0.21	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	1050694	Tablets			
A.W.C Counter :	1009384	Tablets			
HEP :	3989 (0.4%)	Tablets	LEP :	5609 (0.6%)	Tablets
GOOD :	999786 (99.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	05 Hour 03 Min 38 Sec
Total Counter :	1050694	Total Running Time :	1582 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.62	kN	No		
HEP :	27.0 %	15.26	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.26	kN	Yes	15	Times
Ref :		12.02	kN			
LCP :	2.0 %	11.78	kN	Yes	15	Times
LEP :	27.0 %	8.77	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.56	kN	Min :	1.14	kN	Punch NO.;	16
SD :	12.60	%	Max :	1.94	kN	Punch NO.;	2
Mean Main Pressure :	11.81	kN	Min :	8.72	kN	Punch NO.;	49
SD :	10.20	%	Max :	14.34	kN	Punch NO.;	34
Filling Depth :	Increase ;	778	Times	Decrease ;	646	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.10	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.56	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.667	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	9
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.14	kN		
	Max ;	0.23	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	1050694	Tablets			
A.W.C Counter :	1009449	Tablets			
HEP :	3989 (0.4%)	Tablets	LEP :	5610 (0.6%)	Tablets
GOOD :	999850 (99.0%)	Tablets			