

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	12 Hour 38 Min 56 Sec
Total Counter :	2829464	Total Running Time :	1590 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.49	kN	No		
HEP :	30.0 %	17.49	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	13.73	kN	Yes	15 Times	
Ref :		13.46	kN			
LCP :	2.0 %	13.19	kN	Yes	15 Times	
LEP :	30.0 %	9.42	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	9.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.09	kN	Min :	1.71	kN	Punch NO.;	65
SD :	8.10	%	Max :	2.47	kN	Punch NO.;	40
Mean Main Pressure :	13.19	kN	Min :	10.66	kN	Punch NO.;	49
SD :	7.10	%	Max :	14.68	kN	Punch NO.;	24
Filling Depth :	Increase ;	653	Times	Decrease ;	753	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.11	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.22	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	11
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	2829464	Tablets			
A.W.C Counter :	2777187	Tablets			
HEP :	5444 (0.2%)	Tablets	LEP :	7513 (0.3%)	Tablets
GOOD :	2764230 (99.5%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	12 Hour 38 Min 56 Sec
Total Counter :	2829464	Total Running Time :	1590 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	21	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.96	kN	No		
HEP :	30.0 %	16.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.31	kN	Yes 15	Times	
Ref :		13.05	kN			
LCP :	2.0 %	12.78	kN	Yes 15	Times	
LEP :	30.0 %	9.13	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.13	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.42	kN	Punch NO.;	29
SD :	10.90	%	Max :	2.24	kN	Punch NO.;	40
Mean Main Pressure :	13.02	kN	Min :	10.08	kN	Punch NO.;	49
SD :	9.40	%	Max :	15.83	kN	Punch NO.;	34
Filling Depth :	Increase ;	623	Times	Decrease ;	616	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	26
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	2829464	Tablets			
A.W.C Counter :	2777187	Tablets			
HEP :	5444 (0.2%)	Tablets	LEP :	7513 (0.3%)	Tablets
GOOD :	2764230 (99.5%)	Tablets			