

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	15 Hour 25 Min 19 Sec
Total Counter :	3479716	Total Running Time :	1593 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.00	kN	No		
HEP :	30.0 %	18.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.12	kN	Yes 15	Times	
Ref :		13.84	kN			
LCP :	2.0 %	13.57	kN	Yes 15	Times	
LEP :	30.0 %	9.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.18	kN	Min :	1.77	kN	Punch NO.;	16
SD :	9.70	%	Max :	2.59	kN	Punch NO.;	56
Mean Main Pressure :	14.17	kN	Min :	11.28	kN	Punch NO.;	49
SD :	7.60	%	Max :	16.41	kN	Punch NO.;	39
Filling Depth :	Increase ;	950	Times	Decrease ;	1059	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.11	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.16	mm	Current Cam :	Cam B	
Main Air pressure :	0.737	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	11
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.14	kN		
	Max ;	0.21	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	3479716	Tablets			
A.W.C Counter :	3426841	Tablets			
HEP :	5589 (0.2%)	Tablets	LEP :	7826 (0.2%)	Tablets
GOOD :	3413426 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	15 Hour 25 Min 19 Sec
Total Counter :	3479716	Total Running Time :	1593 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	21	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.96	kN	No		
HEP :	30.0 %	16.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.31	kN	Yes 15	Times	
Ref :		13.05	kN			
LCP :	2.0 %	12.78	kN	Yes 15	Times	
LEP :	30.0 %	9.13	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.13	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.72	kN	Min :	1.36	kN	Punch NO.;	65
SD :	12.00	%	Max :	2.22	kN	Punch NO.;	50
Mean Main Pressure :	12.81	kN	Min :	9.54	kN	Punch NO.;	49
SD :	9.20	%	Max :	15.98	kN	Punch NO.;	34
Filling Depth :	Increase ;	914	Times	Decrease ;	909	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.48	mm	Current Cam :	Cam B	
Main Air pressure :	0.737	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	9
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.14	kN		
	Max ;	0.21	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	3479716	Tablets			
A.W.C Counter :	3426841	Tablets			
HEP :	5589 (0.2%)	Tablets	LEP :	7826 (0.2%)	Tablets
GOOD :	3413426 (99.6%)	Tablets			