

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | PANTO 20<br>MG,STKQ1A00 |
| User ID :        | sj97904       | Batch NO. :          | KQM2501920              |
| Print Interval : | 50000 Tablets | Running Time :       | 21 Hour 11 Min 00 Sec   |
| Total Counter :  | 4830610       | Total Running Time : | 1599 Hour 3 Min         |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |                   |         |                    |              |           |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 26                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |             | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |             | 5500000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |             | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |             |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 25                | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 15                | Min     | Supply Time ;      | 2.0          | Sec       |
| Powder Supply Time :               |             | 30.0              | Sec     |                    |              |           |
| Initial Reject Time :              |             | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |           |
|                                    |             |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 18.01             | kN      | No                 |              |           |
| HEP :                              | 30.0 %      | 18.01             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 14.13             | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 13.85             | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 13.58             | kN      | Yes 15             | Times        |           |
| LEP :                              | 30.0 %      | 9.70              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 9.70              | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |                   |         | Yes                |              |           |
| Pre HSP                            |             | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |                   |         |                    |              |           |

### Pressure Data

|                      |            |      |       |            |      |            |    |
|----------------------|------------|------|-------|------------|------|------------|----|
| Mean Pre Pressure :  | 2.31       | kN   | Min : | 1.83       | kN   | Punch NO.; | 15 |
| SD :                 | 8.90       | %    | Max : | 2.68       | kN   | Punch NO.; | 50 |
| Mean Main Pressure : | 13.91      | kN   | Min : | 11.37      | kN   | Punch NO.; | 62 |
| SD :                 | 8.70       | %    | Max : | 16.19      | kN   | Punch NO.; | 53 |
| Filling Depth :      | Increase ; | 1462 | Times | Decrease ; | 1573 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 30      | RPM | Capacity :       | 234000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 8        | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 4.05    | mm  | Pre Thickness ;  | 1.06     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 3.53    | mm  | Main Thickness ; | 0.53     | mm           |
| Filling Depth :               | 6.27    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.795   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 21      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 8       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.18 | kN | Max Punch ; | 29 |
| Lower Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |
| Ejection Force : | Average ; | 0.12 | kN |             |    |
|                  | Max ;     | 0.20 | kN | Max Punch ; | 25 |

### Tablet Data (N/A)

|                 |                 |         |       |             |         |
|-----------------|-----------------|---------|-------|-------------|---------|
| Total Counter : | 4830610         | Tablets |       |             |         |
| A.W.C Counter : | 4775142         | Tablets |       |             |         |
| HEP :           | 5829 (0.1%)     | Tablets | LEP : | 8257 (0.2%) | Tablets |
| GOOD :          | 4761056 (99.7%) | Tablets |       |             |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | PANTO 20<br>MG,STKQ1A00 |
| User ID :        | sj97904       | Batch NO. :          | KQM2501920              |
| Print Interval : | 50000 Tablets | Running Time :       | 21 Hour 11 Min 00 Sec   |
| Total Counter :  | 4830610       | Total Running Time : | 1599 Hour 3 Min         |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |                   |         |                    |       |                      |
|------------------------------------|--------|-------------------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 27                | %       | Manual ;           | 14    | RPM                  |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min : | 2.50 mm              |
| Target Quantity :                  |        | 5500000           | Tablets |                    | Max : | 8.00 mm              |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |                   |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 25                | Min     | Supply Time ;      | 1.0   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 15                | Min     | Supply Time ;      | 2.0   | Sec                  |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 1                 | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |       |                      |
|                                    |        |                   |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 % | 17.90             | kN      | No                 |       |                      |
| HEP :                              | 30.0 % | 17.90             | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %  | 14.04             | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 13.77             | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 13.49             | kN      | Yes                | 15    | Times                |
| LEP :                              | 30.0 % | 9.64              | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 30.0 % | 9.64              | kN      | No                 |       |                      |
| SD limit :                         | 35.0 % |                   |         | Yes                |       |                      |
| Pre HSP                            |        | 30.00             | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 1     | Rotations            |
| Empty Punch No. :                  | N      |                   |         |                    |       |                      |

### Pressure Data

|                      |            |      |       |            |      |            |    |
|----------------------|------------|------|-------|------------|------|------------|----|
| Mean Pre Pressure :  | 1.77       | kN   | Min : | 1.28       | kN   | Punch NO.; | 11 |
| SD :                 | 11.60      | %    | Max : | 2.22       | kN   | Punch NO.; | 1  |
| Mean Main Pressure : | 13.68      | kN   | Min : | 11.78      | kN   | Punch NO.; | 49 |
| SD :                 | 7.60       | %    | Max : | 15.78      | kN   | Punch NO.; | 50 |
| Filling Depth :      | Increase ; | 1425 | Times | Decrease ; | 1430 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 30      | RPM | Capacity :       | 234000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 8        | RPM          |
| Pre Upper Punch Position ;    | 3.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 4.05    | mm  | Pre Thickness ;  | 1.05     | mm           |
| Main Upper Punch Position ;   | 3.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 3.53    | mm  | Main Thickness ; | 0.53     | mm           |
| Filling Depth :               | 6.49    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.795   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 21      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 8       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.21 | kN | Max Punch ; | 29 |
| Lower Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |
| Ejection Force : | Average ; | 0.12 | kN |             |    |
|                  | Max ;     | 0.20 | kN | Max Punch ; | 25 |

### Tablet Data (N/A)

|                 |                    |         |       |             |         |
|-----------------|--------------------|---------|-------|-------------|---------|
| Total Counter : | 4830610            | Tablets |       |             |         |
| A.W.C Counter : | 4775142            | Tablets |       |             |         |
| HEP :           | 5829 (0.1%)        | Tablets | LEP : | 8257 (0.2%) | Tablets |
| GOOD :          | 4761056<br>(99.7%) | Tablets |       |             |         |