

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502020
Print Interval :	50000 Tablets	Running Time :	03 Hour 25 Min 10 Sec
Total Counter :	800634	Total Running Time :	1604 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	23	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.01	kN	No		
HEP :	30.0 %	18.01	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.13	kN	Yes	15	Times
Ref :		13.85	kN			
LCP :	2.0 %	13.58	kN	Yes	15	Times
LEP :	30.0 %	9.70	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.39	kN	Min :	2.00	kN	Punch NO.;	13
SD :	8.40	%	Max :	2.92	kN	Punch NO.;	40
Mean Main Pressure :	13.93	kN	Min :	11.00	kN	Punch NO.;	65
SD :	8.60	%	Max :	16.23	kN	Punch NO.;	28
Filling Depth :	Increase ;	1783	Times	Decrease ;	2127	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.06	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	11
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.26	kN	Max Punch ;	40

Tablet Data (N/A)

Total Counter :	800634	Tablets			
A.W.C Counter :	794254	Tablets			
HEP :	12 (0.0%)	Tablets	LEP :	101 (0.0%)	Tablets
GOOD :	794141 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502020
Print Interval :	50000 Tablets	Running Time :	03 Hour 25 Min 10 Sec
Total Counter :	800634	Total Running Time :	1604 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.90	kN	No		
HEP :	30.0 %	17.90	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.04	kN	Yes	15	Times
Ref :		13.77	kN			
LCP :	2.0 %	13.49	kN	Yes	15	Times
LEP :	30.0 %	9.64	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.64	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.33	kN	Punch NO.;	11
SD :	11.80	%	Max :	2.29	kN	Punch NO.;	40
Mean Main Pressure :	13.83	kN	Min :	11.08	kN	Punch NO.;	60
SD :	9.60	%	Max :	16.75	kN	Punch NO.;	28
Filling Depth :	Increase ;	1577	Times	Decrease ;	1574	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.42	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	11
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.26	kN	Max Punch ;	40

Tablet Data (N/A)

Total Counter :	800634	Tablets			
A.W.C Counter :	794254	Tablets			
HEP :	12 (0.0%)	Tablets	LEP :	101 (0.0%)	Tablets
GOOD :	794141 (100.0%)	Tablets			