

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502110
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 51 Sec
Total Counter :	200206	Total Running Time :	1625 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.60	kN	No		
HEP :	30.0 %	17.60	kN	Yes	10	Rotations
HCP :	2.0 %	13.81	kN	Yes	15	Times
Ref :		13.54	kN			
LCP :	2.0 %	13.27	kN	Yes	15	Times
LEP :	30.0 %	9.48	kN	Yes	10	Rotations
LSP :	30.0 %	9.48	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.26	kN	Min :	1.21	kN	Punch NO.;	62
		2.30	%	Max :	1.32	kN	Punch NO.;	1
Mean Main Pressure :	SD :	13.47	kN	Min :	13.03	kN	Punch NO.;	29
		1.70	%	Max :	14.14	kN	Punch NO.;	72
Filling Depth :	Increase ;	29	Times	Decrease ;	49	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	9.31	mm	Current Cam :	Cam C	
Main Air pressure :	0.745	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	42
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	67
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	200206	Tablets			
A.W.C Counter :	190144	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	190139 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502110
Print Interval :	50000 Tablets	Running Time :	00 Hour 46 Min 51 Sec
Total Counter :	200206	Total Running Time :	1625 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.01	kN	No		
HEP :	30.0 %	16.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.56	kN	Yes 15	Times	
Ref :		12.31	kN			
LCP :	2.0 %	12.07	kN	Yes 15	Times	
LEP :	30.0 %	8.62	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.62	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.90	kN	Min :	0.86	kN	Punch NO.;	62
SD :	2.00	%	Max :	0.95	kN	Punch NO.;	20
Mean Main Pressure :	12.42	kN	Min :	11.47	kN	Punch NO.;	13
SD :	3.40	%	Max :	13.62	kN	Punch NO.;	1
Filling Depth :	Increase ;	26	Times	Decrease ;	18	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	9.14	mm	Current Cam :	Cam C	
Main Air pressure :	0.745	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	42
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	67
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	200206	Tablets			
A.W.C Counter :	190144	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	190139 (100.0%)	Tablets			