

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	vg96371	Batch NO. :	SHM2502210
Print Interval :	50000 Tablets	Running Time :	07 Hour 55 Min 55 Sec
Total Counter :	2051552	Total Running Time :	1644 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.32	kN	No		
HEP :	30.0 %	19.32	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.16	kN	Yes 15	Times	
Ref :		14.86	kN			
LCP :	2.0 %	14.57	kN	Yes 15	Times	
LEP :	30.0 %	10.40	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.40	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.39	kN	Min :	1.36	kN	Punch NO.;	58
		1.10	%	Max :	1.43	kN	Punch NO.;	13
Mean Main Pressure :		14.85	kN	Min :	13.91	kN	Punch NO.;	6
	SD :	3.30	%	Max :	16.24	kN	Punch NO.;	62
Filling Depth :	Increase ;	307	Times	Decrease ;	438	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	9.26	mm	Current Cam :	Cam C	
Main Air pressure :	0.747	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	44
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	2051552	Tablets			
A.W.C Counter :	2047700	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2047700 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	vg96371	Batch NO. :	SHM2502210
Print Interval :	50000 Tablets	Running Time :	07 Hour 55 Min 55 Sec
Total Counter :	2051552	Total Running Time :	1644 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.75	kN	No		
HEP :	30.0 %	17.75	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.92	kN	Yes	15	Times
Ref :		13.65	kN			
LCP :	2.0 %	13.38	kN	Yes	15	Times
LEP :	30.0 %	9.56	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.92	kN	Min :	0.88	kN	Punch NO.;	6
SD :	2.40	%	Max :	0.98	kN	Punch NO.;	53
Mean Main Pressure :	13.40	kN	Min :	12.39	kN	Punch NO.;	41
SD :	4.70	%	Max :	14.96	kN	Punch NO.;	32
Filling Depth :	Increase ;	336	Times	Decrease ;	330	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	9.10	mm	Current Cam :	Cam C	
Main Air pressure :	0.747	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	44
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	2051552	Tablets			
A.W.C Counter :	2047700	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2047700 (100.0%)	Tablets			