

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA100MG<br>STSH4B00 |
| User ID :        | ms88737       | Batch NO. :          | SHM2502310              |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 56 Min 31 Sec   |
| Total Counter :  | 2051902       | Total Running Time : | 1655 Hour 43 Min        |
| Station :        | Station 1     |                      |                         |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 43       | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 3000000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.600    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 60       | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 40       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 30.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 1        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 2.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 4.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 19.16    | kN      | No                 |              |           |
| HEP :                              | 30.0 %      | 19.16    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 15.03    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 14.74    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 14.45    | kN      | Yes 15             | Times        |           |
| LEP :                              | 30.0 %      | 10.32    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 10.32    | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 30.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 1.42       | kN  | Min : | 1.39       | kN  | Punch NO.; | 62 |
| SD :                 | 1.00       | %   | Max : | 1.46       | kN  | Punch NO.; | 44 |
| Mean Main Pressure : | 14.79      | kN  | Min : | 13.99      | kN  | Punch NO.; | 19 |
| SD :                 | 2.70       | %   | Max : | 15.74      | kN  | Punch NO.; | 74 |
| Filling Depth :      | Increase ; | 479 | Times | Decrease ; | 585 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 12       | RPM          |
| Pre Upper Punch Position ;    | 2.50    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.58    | mm  | Pre Thickness ;  | 3.08     | mm           |
| Main Upper Punch Position ;   | 2.50    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.50    | mm  | Main Thickness ; | 2.00     | mm           |
| Filling Depth :               | 9.41    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.807   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 44      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 26      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.02 | kN | Max Punch ; | 30 |
| Lower Punch :    | Average ; | 0.12 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 44 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 17 |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 2051902             | Tablets |       |            |         |
| A.W.C Counter : | 2044677             | Tablets |       |            |         |
| HEP :           | 16 (0.0%)           | Tablets | LEP : | 122 (0.0%) | Tablets |
| GOOD :          | 2044539<br>(100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                         |
|------------------|---------------|----------------------|-------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | SERTRA100MG<br>STSH4B00 |
| User ID :        | ms88737       | Batch NO. :          | SHM2502310              |
| Print Interval : | 50000 Tablets | Running Time :       | 07 Hour 56 Min 31 Sec   |
| Total Counter :  | 2051902       | Total Running Time : | 1655 Hour 43 Min        |
| Station :        | Station 2     |                      |                         |

### Setting Value

|                                    |        |           |         |                    |              |           |
|------------------------------------|--------|-----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 48        | %       | Manual ;           | 14           | RPM       |
| Filling Cam :                      |        | Cam C     |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |        | 8.5-14mm  |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |        | 3000000   | Tablets |                    |              |           |
| Air Pressure Low Limit :           |        | 0.600     | MPa     |                    |              |           |
| Oil Lubrication :                  |        |           |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 60        | Min     | Supply Time ;      | 1.0          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40        | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 30.0      | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1         | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00      | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00      | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00      | kN      |                    |              |           |
|                                    |        |           |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 16.75     | kN      | No                 |              |           |
| HEP :                              | 30.0 % | 16.75     | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 13.14     | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 12.88     | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 12.63     | kN      | Yes 15             | Times        |           |
| LEP :                              | 30.0 % | 9.02      | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 9.02      | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |           |         | Yes                |              |           |
| Pre HSP                            |        | 30.00     | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |           |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 0.97       | kN  | Min : | 0.94       | kN  | Punch NO.; | 75 |
| SD :                 | 1.80       | %   | Max : | 1.02       | kN  | Punch NO.; | 21 |
| Mean Main Pressure : | 12.79      | kN  | Min : | 11.47      | kN  | Punch NO.; | 41 |
| SD :                 | 5.00       | %   | Max : | 14.38      | kN  | Punch NO.; | 32 |
| Filling Depth :      | Increase ; | 638 | Times | Decrease ; | 809 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 258720   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 13       | RPM          |
| Pre Upper Punch Position ;    | 2.50    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.50    | mm  | Pre Thickness ;  | 3.00     | mm           |
| Main Upper Punch Position ;   | 2.50    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.55    | mm  | Main Thickness ; | 2.05     | mm           |
| Filling Depth :               | 9.52    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.807   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 44      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 26      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | On       |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.02 | kN | Max Punch ; | 70 |
| Lower Punch :    | Average ; | 0.12 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 44 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 17 |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 2051902             | Tablets |       |            |         |
| A.W.C Counter : | 2044677             | Tablets |       |            |         |
| HEP :           | 16 (0.0%)           | Tablets | LEP : | 122 (0.0%) | Tablets |
| GOOD :          | 2044539<br>(100.0%) | Tablets |       |            |         |