

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502510
Print Interval :	50000 Tablets	Running Time :	09 Hour 05 Min 44 Sec
Total Counter :	2351594	Total Running Time :	1680 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.21	kN	No		
HEP :	30.0 %	20.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.86	kN	Yes 15	Times	
Ref :		15.54	kN			
LCP :	2.0 %	15.23	kN	Yes 15	Times	
LEP :	30.0 %	10.88	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.51	kN	Min :	1.48	kN	Punch NO.;	34
SD :	1.30	%	Max :	1.57	kN	Punch NO.;	1
Mean Main Pressure :	15.55	kN	Min :	14.67	kN	Punch NO.;	47
SD :	2.60	%	Max :	16.33	kN	Punch NO.;	51
Filling Depth :	Increase ;	514	Times	Decrease ;	691	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	2.04	mm
Filling Depth :	9.43	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	38
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	44
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	64

Tablet Data (N/A)

Total Counter :	2351594	Tablets			
A.W.C Counter :	2348610	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2348610 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502510
Print Interval :	50000 Tablets	Running Time :	09 Hour 05 Min 44 Sec
Total Counter :	2351594	Total Running Time :	1680 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	14	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.03	kN	No		
HEP :	30.0 %	18.03	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.14	kN	Yes	15	Times
Ref :		13.87	kN			
LCP :	2.0 %	13.59	kN	Yes	15	Times
LEP :	30.0 %	9.71	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.71	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.24	kN	Min :	1.19	kN	Punch NO.;	34
SD :	1.40	%	Max :	1.29	kN	Punch NO.;	77
Mean Main Pressure :	13.99	kN	Min :	12.81	kN	Punch NO.;	47
SD :	4.50	%	Max :	16.18	kN	Punch NO.;	31
Filling Depth :	Increase ;	707	Times	Decrease ;	916	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	2.18	mm
Filling Depth :	9.59	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	38
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	44
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	64

Tablet Data (N/A)

Total Counter :	2351594	Tablets			
A.W.C Counter :	2348610	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2348610 (100.0%)	Tablets			