

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	00 Hour 51 Min 23 Sec
Total Counter :	200112	Total Running Time :	1694 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.28	kN	No		
HEP :	25.0 %	14.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.99	kN	Yes 15	Times	
Ref :		11.75	kN			
LCP :	2.0 %	11.52	kN	Yes 15	Times	
LEP :	25.0 %	8.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.03	kN	Min :	2.69	kN	Punch NO.;	26
SD :	5.60	%	Max :	3.46	kN	Punch NO.;	15
Mean Main Pressure :	11.70	kN	Min :	10.24	kN	Punch NO.;	17
SD :	5.30	%	Max :	13.43	kN	Punch NO.;	9
Filling Depth :	Increase ; 61	Times	Decrease ; 53	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.15	mm	Pre Thickness ;	1.15	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.14	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.14	kN	Max Punch ;	39
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.32	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	200112	Tablets			
A.W.C Counter :	192801	Tablets			
HEP :	38 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	192728 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	00 Hour 51 Min 23 Sec
Total Counter :	200112	Total Running Time :	1694 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	24	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.65	kN	No		
HEP :	25.0 %	16.01	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.07	kN	Yes	15	Times
Ref :		12.81	kN			
LCP :	2.0 %	12.55	kN	Yes	15	Times
LEP :	25.0 %	9.61	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.80	kN	Min :	2.33	kN	Punch NO.;	24
SD :	9.00	%	Max :	3.49	kN	Punch NO.;	62
Mean Main Pressure :	12.93	kN	Min :	10.73	kN	Punch NO.;	26
SD :	7.60	%	Max :	15.63	kN	Punch NO.;	62
Filling Depth :	Increase ;	40	Times	Decrease ;	47	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.27	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	48
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.32	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.12	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	200112	Tablets			
A.W.C Counter :	192801	Tablets			
HEP :	38 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	192728 (100.0%)	Tablets			