

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	19 Hour 45 Min 42 Sec
Total Counter :	3944354	Total Running Time :	1713 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.14	kN	No		
HEP :	25.0 %	14.56	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.88	kN	Yes 15	Times	
Ref :		11.65	kN			
LCP :	2.0 %	11.42	kN	Yes 15	Times	
LEP :	25.0 %	8.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.15	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.60	kN	Min :	1.25	kN	Punch NO.;	4
SD :	9.60	%	Max :	1.93	kN	Punch NO.;	55
Mean Main Pressure :	11.71	kN	Min :	9.99	kN	Punch NO.;	4
SD :	6.80	%	Max :	13.47	kN	Punch NO.;	57
Filling Depth :	Increase ;	114	Times	Decrease ;	133	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.63	mm	Main Thickness ;	0.64	mm
Filling Depth :	6.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	54
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.30	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	3944354	Tablets			
A.W.C Counter :	3925333	Tablets			
HEP :	1714 (0.0%)	Tablets	LEP :	1066 (0.0%)	Tablets
GOOD :	3922553 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	19 Hour 45 Min 42 Sec
Total Counter :	3944354	Total Running Time :	1713 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.42	kN	No		
HEP :	25.0 %	15.79	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.88	kN	Yes	15	Times
Ref :		12.63	kN			
LCP :	2.0 %	12.38	kN	Yes	15	Times
LEP :	25.0 %	9.47	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.84	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.76	kN	Min :	1.43	kN	Punch NO.;	26
SD :	8.10	%	Max :	2.07	kN	Punch NO.;	58
Mean Main Pressure :	12.45	kN	Min :	10.20	kN	Punch NO.;	26
SD :	6.90	%	Max :	14.52	kN	Punch NO.;	48
Filling Depth :	Increase ;	207	Times	Decrease ;	177	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	55
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.30	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	3944354	Tablets			
A.W.C Counter :	3925333	Tablets			
HEP :	1714 (0.0%)	Tablets	LEP :	1066 (0.0%)	Tablets
GOOD :	3922553 (99.9%)	Tablets			