

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	23 Hour 20 Min 34 Sec
Total Counter :	4644764	Total Running Time :	1717 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.58	kN	No		
HEP :	25.0 %	15.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.01	kN	Yes 15	Times	
Ref :		12.75	kN			
LCP :	2.0 %	12.50	kN	Yes 15	Times	
LEP :	25.0 %	9.56	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.93	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.72	kN	Min :	1.36	kN	Punch NO.;	38
SD :	8.00	%	Max :	2.00	kN	Punch NO.;	19
Mean Main Pressure :	12.87	kN	Min :	11.14	kN	Punch NO.;	38
SD :	6.10	%	Max :	14.63	kN	Punch NO.;	57
Filling Depth :	Increase ; 232	Times	Decrease ; 240	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.61	mm
Filling Depth :	6.29	mm	Current Cam :	Cam B	
Main Air pressure :	0.716	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	14
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.29	kN	Max Punch ;	37
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	7

Tablet Data (N/A)

Total Counter :	4644764	Tablets			
A.W.C Counter :	4624507	Tablets			
HEP :	1856 (0.0%)	Tablets	LEP :	1529 (0.0%)	Tablets
GOOD :	4621122 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	23 Hour 20 Min 34 Sec
Total Counter :	4644764	Total Running Time :	1717 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.70	kN	No		
HEP :	25.0 %	16.05	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.10	kN	Yes	15	Times
Ref :		12.84	kN			
LCP :	2.0 %	12.59	kN	Yes	15	Times
LEP :	25.0 %	9.63	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.99	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.82	kN	Min :	1.56	kN	Punch NO.;	17
SD :	6.40	%	Max :	2.06	kN	Punch NO.;	58
Mean Main Pressure :	12.81	kN	Min :	10.79	kN	Punch NO.;	17
SD :	5.50	%	Max :	14.64	kN	Punch NO.;	65
Filling Depth :	Increase ;	408	Times	Decrease ;	349	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.62	mm	Current Cam :	Cam B	
Main Air pressure :	0.716	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	14
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.29	kN	Max Punch ;	37
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	7

Tablet Data (N/A)

Total Counter :	4644764	Tablets			
A.W.C Counter :	4624507	Tablets			
HEP :	1856 (0.0%)	Tablets	LEP :	1529 (0.0%)	Tablets
GOOD :	4621122 (99.9%)	Tablets			