

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	21 Hour 13 Min 42 Sec
Total Counter :	4152086	Total Running Time :	1742 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.01	kN	No		
HEP :	25.0 %	16.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.35	kN	Yes 15	Times	
Ref :		13.08	kN			
LCP :	2.0 %	12.82	kN	Yes 15	Times	
LEP :	25.0 %	9.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.73	kN	Min :	1.37	kN	Punch NO.;	17
SD :	9.00	%	Max :	2.01	kN	Punch NO.;	56
Mean Main Pressure :	13.23	kN	Min :	11.20	kN	Punch NO.;	17
SD :	5.80	%	Max :	14.75	kN	Punch NO.;	23
Filling Depth :	Increase ;	1405	Times	Decrease ;	1440	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.34	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.57	mm	Main Thickness ;	0.58	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.22	kN	Max Punch ;	14
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.30	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	4152086	Tablets			
A.W.C Counter :	4140529	Tablets			
HEP :	517 (0.0%)	Tablets	LEP :	558 (0.0%)	Tablets
GOOD :	4139454 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	21 Hour 13 Min 42 Sec
Total Counter :	4152086	Total Running Time :	1742 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.16	kN	No		
HEP :	25.0 %	16.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.47	kN	Yes 15	Times	
Ref :		13.20	kN			
LCP :	2.0 %	12.94	kN	Yes 15	Times	
LEP :	25.0 %	9.90	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.82	kN	Min :	1.53	kN	Punch NO.;	26
SD :	6.30	%	Max :	2.10	kN	Punch NO.;	35
Mean Main Pressure :	13.02	kN	Min :	10.58	kN	Punch NO.;	26
SD :	6.10	%	Max :	14.96	kN	Punch NO.;	35
Filling Depth :	Increase ;	1019	Times	Decrease ;	968	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.34	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.63	mm	Main Thickness ;	0.64	mm
Filling Depth :	6.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	51
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.30	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	4152086	Tablets			
A.W.C Counter :	4140529	Tablets			
HEP :	517 (0.0%)	Tablets	LEP :	558 (0.0%)	Tablets
GOOD :	4139454 (100.0%)	Tablets			