

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	03 Hour 37 Min 21 Sec
Total Counter :	5402770	Total Running Time :	1749 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	32	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.82	kN	No		
HEP :	25.0 %	17.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.98	kN	Yes 15	Times	
Ref :		13.71	kN			
LCP :	2.0 %	13.43	kN	Yes 15	Times	
LEP :	25.0 %	10.28	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.44	kN	Punch NO.;	52
SD :	7.20	%	Max :	2.10	kN	Punch NO.;	43
Mean Main Pressure :	13.96	kN	Min :	11.81	kN	Punch NO.;	17
SD :	5.50	%	Max :	15.84	kN	Punch NO.;	43
Filling Depth :	Increase ;	1647	Times	Decrease ;	1682	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.34	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.57	mm	Main Thickness ;	0.58	mm
Filling Depth :	6.38	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	14
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	13
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	5402770	Tablets			
A.W.C Counter :	5390493	Tablets			
HEP :	579 (0.0%)	Tablets	LEP :	618 (0.0%)	Tablets
GOOD :	5389296 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	03 Hour 37 Min 21 Sec
Total Counter :	5402770	Total Running Time :	1749 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	24	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.79	kN	No		
HEP :	25.0 %	17.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.96	kN	Yes 15	Times	
Ref :		13.68	kN			
LCP :	2.0 %	13.41	kN	Yes 15	Times	
LEP :	25.0 %	10.26	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.86	kN	Min :	1.59	kN	Punch NO.;	26
SD :	6.20	%	Max :	2.12	kN	Punch NO.;	15
Mean Main Pressure :	13.71	kN	Min :	11.83	kN	Punch NO.;	26
SD :	5.50	%	Max :	15.32	kN	Punch NO.;	18
Filling Depth :	Increase ;	1111	Times	Decrease ;	1058	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.34	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.63	mm	Main Thickness ;	0.64	mm
Filling Depth :	6.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	14
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.21	kN	Max Punch ;	13
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	5402770	Tablets			
A.W.C Counter :	5390493	Tablets			
HEP :	579 (0.0%)	Tablets	LEP :	618 (0.0%)	Tablets
GOOD :	5389296 (100.0%)	Tablets			