

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	yu98249	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	06 Hour 10 Min 56 Sec
Total Counter :	559784	Total Running Time :	1755 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.55	kN	No		
HEP :	25.0 %	25.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.83	kN	Yes 15	Times	
Ref :		20.42	kN			
LCP :	2.0 %	20.01	kN	Yes 15	Times	
LEP :	25.0 %	15.32	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.13	kN	Min :	2.15	kN	Punch NO.;	33
SD :	18.70	%	Max :	4.61	kN	Punch NO.;	2
Mean Main Pressure :	20.27	kN	Min :	17.04	kN	Punch NO.;	33
SD :	9.20	%	Max :	24.64	kN	Punch NO.;	2
Filling Depth :	Increase ; 207	Times	Decrease ;	222	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.40	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.32	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.803	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	1
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.31	kN	Max Punch ;	1
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	559784	Tablets			
A.W.C Counter :	556878	Tablets			
HEP :	419 (0.1%)	Tablets	LEP :	193 (0.0%)	Tablets
GOOD :	556266 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	yu98249	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	06 Hour 10 Min 56 Sec
Total Counter :	559784	Total Running Time :	1755 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	124	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.32	kN	No		
HEP :	25.0 %	28.20	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	23.01	kN	Yes	15	Times
Ref :		22.56	kN			
LCP :	2.0 %	22.11	kN	Yes	15	Times
LEP :	25.0 %	16.92	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.22	kN	Min :	2.44	kN	Punch NO.;	33
SD :	9.60	%	Max :	3.77	kN	Punch NO.;	11
Mean Main Pressure :	22.10	kN	Min :	19.59	kN	Punch NO.;	33
SD :	4.40	%	Max :	24.12	kN	Punch NO.;	11
Filling Depth :	Increase ;	104	Times	Decrease ;	117	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.42	mm	Main Thickness ;	0.62	mm
Filling Depth :	6.99	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.803	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	1
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.34	kN	Max Punch ;	1
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	559784	Tablets			
A.W.C Counter :	556878	Tablets			
HEP :	419 (0.1%)	Tablets	LEP :	193 (0.0%)	Tablets
GOOD :	556266 (99.9%)	Tablets			