

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	sj97904	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	07 Hour 14 Min 16 Sec
Total Counter :	659836	Total Running Time :	1756 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.55	kN	No		
HEP :	25.0 %	25.53	kN	Yes	10	Rotations
HCP :	2.0 %	20.83	kN	Yes	15	Times
Ref :		20.42	kN			
LCP :	2.0 %	20.01	kN	Yes	15	Times
LEP :	25.0 %	15.32	kN	Yes	10	Rotations
LSP :	30.0 %	14.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.10	kN	Min :	2.11	kN	Punch NO.;	18
SD :	13.90	%	Max :	4.38	kN	Punch NO.;	1
Mean Main Pressure :	20.17	kN	Min :	16.75	kN	Punch NO.;	18
SD :	6.40	%	Max :	23.80	kN	Punch NO.;	2
Filling Depth :	Increase ;	317	Times	Decrease ;	334	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.40	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.27	mm	Current Cam :	Cam B	
Main Air pressure :	0.812	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	1
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.41	kN	Max Punch ;	1
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	659836	Tablets			
A.W.C Counter :	656942	Tablets			
HEP :	441 (0.1%)	Tablets	LEP :	210 (0.0%)	Tablets
GOOD :	656291 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	sj97904	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	07 Hour 14 Min 16 Sec
Total Counter :	659836	Total Running Time :	1756 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	124	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.32	kN	No		
HEP :	25.0 %	28.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.01	kN	Yes 15	Times	
Ref :		22.56	kN			
LCP :	2.0 %	22.11	kN	Yes 15	Times	
LEP :	25.0 %	16.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.24	kN	Min :	2.50	kN	Punch NO.;	42
SD :	12.40	%	Max :	4.32	kN	Punch NO.;	1
Mean Main Pressure :	22.11	kN	Min :	19.24	kN	Punch NO.;	10
SD :	5.70	%	Max :	25.45	kN	Punch NO.;	1
Filling Depth :	Increase ; 147	Times	Decrease ;	166	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.42	mm	Main Thickness ;	0.62	mm
Filling Depth :	6.81	mm	Current Cam :	Cam B	
Main Air pressure :	0.812	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	1
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.55	kN	Max Punch ;	1
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	659836	Tablets			
A.W.C Counter :	656942	Tablets			
HEP :	441 (0.1%)	Tablets	LEP :	210 (0.0%)	Tablets
GOOD :	656291 (99.9%)	Tablets			