

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 06 Sec
Total Counter :	1350936	Total Running Time :	1781 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	12	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.50	kN	No		
HEP :	25.0 %	13.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.37	kN	Yes 15	Times	
Ref :		11.15	kN			
LCP :	2.0 %	10.93	kN	Yes 15	Times	
LEP :	25.0 %	8.36	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.81	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.05	kN	Min :	2.01	kN	Punch NO.;	34
SD :	0.80	%	Max :	2.09	kN	Punch NO.;	27
Mean Main Pressure :	11.04	kN	Min :	9.59	kN	Punch NO.;	60
SD :	3.60	%	Max :	11.89	kN	Punch NO.;	28
Filling Depth :	Increase ;	22	Times	Decrease ;	51	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.67	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.19	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.30	kN	Max Punch ;	53
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	35
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	64

Tablet Data (N/A)

Total Counter :	1350936	Tablets			
A.W.C Counter :	1338247	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1338247 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 06 Sec
Total Counter :	1350936	Total Running Time :	1781 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	14	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.04	kN	No		
HEP :	25.0 %	13.50	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	11.02	kN	Yes	15	Times
Ref :		10.80	kN			
LCP :	2.0 %	10.59	kN	Yes	15	Times
LEP :	25.0 %	8.10	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.01	kN	Min :	1.93	kN	Punch NO.;	28
SD :	2.10	%	Max :	2.10	kN	Punch NO.;	51
Mean Main Pressure :	10.92	kN	Min :	9.60	kN	Punch NO.;	60
SD :	3.60	%	Max :	11.67	kN	Punch NO.;	5
Filling Depth :	Increase ;	8	Times	Decrease ;	9	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.82	mm	Main Thickness ;	0.82	mm
Filling Depth :	6.75	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.31	kN	Max Punch ;	7
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	35
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	64

Tablet Data (N/A)

Total Counter :	1350936	Tablets			
A.W.C Counter :	1338247	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1338247 (100.0%)	Tablets			