

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	os190259	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	10 Hour 42 Min 01 Sec
Total Counter :	2501698	Total Running Time :	1785 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	12	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.57	kN	No		
HEP :	25.0 %	14.97	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.21	kN	Yes	15	Times
Ref :		11.97	kN			
LCP :	2.0 %	11.73	kN	Yes	15	Times
LEP :	25.0 %	8.98	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.99	kN	Min :	1.91	kN	Punch NO.;	52
SD :	1.30	%	Max :	2.05	kN	Punch NO.;	28
Mean Main Pressure :	11.96	kN	Min :	10.15	kN	Punch NO.;	60
SD :	3.90	%	Max :	12.60	kN	Punch NO.;	25
Filling Depth :	Increase ;	48	Times	Decrease ;	102	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.36	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	52	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.24	kN	Max Punch ;	47
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	36
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.12	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	2501698	Tablets			
A.W.C Counter :	2487510	Tablets			
HEP :	65 (0.0%)	Tablets	LEP :	350 (0.0%)	Tablets
GOOD :	2487095 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	os190259	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	10 Hour 42 Min 01 Sec
Total Counter :	2501698	Total Running Time :	1785 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	14	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.07	kN	No		
HEP :	25.0 %	13.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.04	kN	Yes 15	Times	
Ref :		10.83	kN			
LCP :	2.0 %	10.61	kN	Yes 15	Times	
LEP :	25.0 %	8.12	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.96	kN	Min :	1.90	kN	Punch NO.;	28
SD :	1.60	%	Max :	2.04	kN	Punch NO.;	30
Mean Main Pressure :	10.95	kN	Min :	9.47	kN	Punch NO.;	60
SD :	3.40	%	Max :	11.70	kN	Punch NO.;	33
Filling Depth :	Increase ;	28	Times	Decrease ;	28	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.78	mm	Main Thickness ;	0.78	mm
Filling Depth :	6.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	52	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.25	kN	Max Punch ;	47
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	36
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.12	kN	Max Punch ;	43

Tablet Data (N/A)

Total Counter :	2501698	Tablets			
A.W.C Counter :	2487510	Tablets			
HEP :	65 (0.0%)	Tablets	LEP :	350 (0.0%)	Tablets
GOOD :	2487095 (100.0%)	Tablets			