

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	00 Hour 58 Min 46 Sec
Total Counter :	161794	Total Running Time :	1799 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.82	kN	No		
HEP :	25.0 %	33.48	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	27.32	kN	Yes	15	Times
Ref :		26.79	kN			
LCP :	2.0 %	26.25	kN	Yes	15	Times
LEP :	25.0 %	20.09	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	18.75	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.21	kN	Min :	1.13	kN	Punch NO.;	24
SD :	2.50	%	Max :	1.28	kN	Punch NO.;	3
Mean Main Pressure :	26.34	kN	Min :	24.05	kN	Punch NO.;	33
SD :	4.00	%	Max :	29.34	kN	Punch NO.;	3
Filling Depth :	Increase ;	8	Times	Decrease ;	15	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.95	mm
Filling Depth :	5.03	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.11	kN	Max Punch ;	11
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	54
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	161794	Tablets			
A.W.C Counter :	144189	Tablets			
HEP :	0 (0%)	Tablets	LEP :	90 (0.1%)	Tablets
GOOD :	144099 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	00 Hour 58 Min 46 Sec
Total Counter :	161794	Total Running Time :	1799 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.13	kN	No		
HEP :	25.0 %	31.86	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	25.99	kN	Yes	15	Times
Ref :		25.48	kN			
LCP :	2.0 %	24.97	kN	Yes	15	Times
LEP :	25.0 %	19.11	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.84	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.18	kN	Min :	1.14	kN	Punch NO.;	6
SD :	2.00	%	Max :	1.24	kN	Punch NO.;	43
Mean Main Pressure :	25.94	kN	Min :	24.67	kN	Punch NO.;	41
SD :	2.70	%	Max :	27.62	kN	Punch NO.;	50
Filling Depth :	Increase ;	2	Times	Decrease ;	1	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.10	mm
Filling Depth :	4.34	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	13
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	54
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	161794	Tablets			
A.W.C Counter :	144189	Tablets			
HEP :	0 (0%)	Tablets	LEP :	90 (0.1%)	Tablets
GOOD :	144099 (99.9%)	Tablets			