

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	03 Hour 36 Min 26 Sec
Total Counter :	611910	Total Running Time :	1801 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.50	kN	No		
HEP :	25.0 %	34.14	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.86	kN	Yes 15	Times	
Ref :		27.31	kN			
LCP :	2.0 %	26.76	kN	Yes 15	Times	
LEP :	25.0 %	20.48	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.12	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.17	kN	Min :	1.12	kN	Punch NO.;	22
SD :	2.20	%	Max :	1.24	kN	Punch NO.;	50
Mean Main Pressure :	27.40	kN	Min :	25.58	kN	Punch NO.;	22
SD :	3.80	%	Max :	30.74	kN	Punch NO.;	50
Filling Depth :	Increase ; 30	Times	Decrease ; 35	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	0.94	mm
Filling Depth :	4.99	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.803	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.17	kN	Max Punch ;	11
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	54
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	611910	Tablets			
A.W.C Counter :	588165	Tablets			
HEP :	139 (0.0%)	Tablets	LEP :	290 (0.0%)	Tablets
GOOD :	587736 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	03 Hour 36 Min 26 Sec
Total Counter :	611910	Total Running Time :	1801 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.67	kN	No		
HEP :	25.0 %	34.29	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.98	kN	Yes 15	Times	
Ref :		27.44	kN			
LCP :	2.0 %	26.89	kN	Yes 15	Times	
LEP :	25.0 %	20.58	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.15	kN	Min :	1.09	kN	Punch NO.;	30
SD :	2.20	%	Max :	1.21	kN	Punch NO.;	17
Mean Main Pressure :	27.34	kN	Min :	25.26	kN	Punch NO.;	63
SD :	3.30	%	Max :	30.00	kN	Punch NO.;	17
Filling Depth :	Increase ;	9	Times	Decrease ;	26	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.11	mm
Filling Depth :	4.35	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.17	kN	Max Punch ;	11
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	9
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	611910	Tablets			
A.W.C Counter :	588165	Tablets			
HEP :	139 (0.0%)	Tablets	LEP :	290 (0.0%)	Tablets
GOOD :	587736 (99.9%)	Tablets			