

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	12 Hour 56 Min 58 Sec
Total Counter :	2212794	Total Running Time :	1811 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.95	kN	No		
HEP :	25.0 %	35.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.99	kN	Yes 15	Times	
Ref :		28.42	kN			
LCP :	2.0 %	27.85	kN	Yes 15	Times	
LEP :	25.0 %	21.32	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.90	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.28	kN	Min :	1.20	kN	Punch NO.;	38
SD :	2.60	%	Max :	1.39	kN	Punch NO.;	17
Mean Main Pressure :	31.08	kN	Min :	28.67	kN	Punch NO.;	38
SD :	3.60	%	Max :	34.56	kN	Punch NO.;	17
Filling Depth :	Increase ; 69	Times	Decrease ;	87	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.95	mm
Filling Depth :	5.36	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.30	kN	Max Punch ;	16
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	60
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	2212794	Tablets			
A.W.C Counter :	2185672	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	643 (0.0%)	Tablets
GOOD :	2184870 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	12 Hour 56 Min 58 Sec
Total Counter :	2212794	Total Running Time :	1811 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.74	kN	No		
HEP :	25.0 %	35.33	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	28.83	kN	Yes	15	Times
Ref :		28.26	kN			
LCP :	2.0 %	27.70	kN	Yes	15	Times
LEP :	25.0 %	21.20	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	19.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.17	kN	Min :	1.12	kN	Punch NO.;	41
SD :	2.50	%	Max :	1.24	kN	Punch NO.;	17
Mean Main Pressure :	28.16	kN	Min :	26.13	kN	Punch NO.;	41
SD :	3.30	%	Max :	30.20	kN	Punch NO.;	17
Filling Depth :	Increase ;	36	Times	Decrease ;	67	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.11	mm
Filling Depth :	4.51	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.30	kN	Max Punch ;	16
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	64
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	30

Tablet Data (N/A)

Total Counter :	2212794	Tablets			
A.W.C Counter :	2185672	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	643 (0.0%)	Tablets
GOOD :	2184870 (100.0%)	Tablets			