

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	06 Hour 25 Min 56 Sec
Total Counter :	1100706	Total Running Time :	1820 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.35	kN	No		
HEP :	25.0 %	32.07	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	26.17	kN	Yes	15	Times
Ref :		25.65	kN			
LCP :	2.0 %	25.14	kN	Yes	15	Times
LEP :	25.0 %	19.24	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.38	kN	Min :	1.26	kN	Punch NO.;	24
SD :	3.30	%	Max :	1.49	kN	Punch NO.;	53
Mean Main Pressure :	25.57	kN	Min :	23.84	kN	Punch NO.;	24
SD :	3.50	%	Max :	28.06	kN	Punch NO.;	43
Filling Depth :	Increase ;	12	Times	Decrease ;	14	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	1.05	mm
Filling Depth :	5.18	mm	Current Cam :	Cam B	
Main Air pressure :	0.793	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.29	kN	Max Punch ;	24
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	29
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	1100706	Tablets			
A.W.C Counter :	1091859	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	260 (0.0%)	Tablets
GOOD :	1091546 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	06 Hour 25 Min 56 Sec
Total Counter :	1100706	Total Running Time :	1820 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.06	kN	No		
HEP :	25.0 %	33.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.51	kN	Yes 15	Times	
Ref :		26.97	kN			
LCP :	2.0 %	26.43	kN	Yes 15	Times	
LEP :	25.0 %	20.23	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.37	kN	Min :	1.26	kN	Punch NO.;	8
SD :	3.50	%	Max :	1.47	kN	Punch NO.;	2
Mean Main Pressure :	27.10	kN	Min :	24.88	kN	Punch NO.;	5
SD :	3.60	%	Max :	29.30	kN	Punch NO.;	50
Filling Depth :	Increase ;	36	Times	Decrease ;	27	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.65	mm	Main Thickness ;	1.15	mm
Filling Depth :	4.45	mm	Current Cam :	Cam B	
Main Air pressure :	0.793	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.28	kN	Max Punch ;	16
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	29
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	1100706	Tablets			
A.W.C Counter :	1091859	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	260 (0.0%)	Tablets
GOOD :	1091546 (100.0%)	Tablets			