

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	08 Hour 28 Min 28 Sec
Total Counter :	1450822	Total Running Time :	1822 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.06	kN	No		
HEP :	25.0 %	32.75	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	26.72	kN	Yes	15	Times
Ref :		26.20	kN			
LCP :	2.0 %	25.67	kN	Yes	15	Times
LEP :	25.0 %	19.65	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	18.34	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.39	kN	Min :	1.28	kN	Punch NO.;	8
SD :	3.40	%	Max :	1.51	kN	Punch NO.;	17
Mean Main Pressure :	26.26	kN	Min :	24.07	kN	Punch NO.;	8
SD :	3.80	%	Max :	29.02	kN	Punch NO.;	26
Filling Depth :	Increase ;	12	Times	Decrease ;	32	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	1.05	mm
Filling Depth :	4.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.793	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.30	kN	Max Punch ;	13
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	54
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	1450822	Tablets			
A.W.C Counter :	1441949	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	260 (0.0%)	Tablets
GOOD :	1441636 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	08 Hour 28 Min 28 Sec
Total Counter :	1450822	Total Running Time :	1822 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.02	kN	No		
HEP :	25.0 %	34.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	28.26	kN	Yes	15	Times
Ref :		27.71	kN			
LCP :	2.0 %	27.15	kN	Yes	15	Times
LEP :	25.0 %	20.78	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	19.40	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.41	kN	Min :	1.33	kN	Punch NO.;	55
SD :	3.40	%	Max :	1.53	kN	Punch NO.;	43
Mean Main Pressure :	28.14	kN	Min :	26.30	kN	Punch NO.;	28
SD :	3.60	%	Max :	31.04	kN	Punch NO.;	43
Filling Depth :	Increase ;	46	Times	Decrease ;	44	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.65	mm	Main Thickness ;	1.15	mm
Filling Depth :	4.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.793	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.30	kN	Max Punch ;	13
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	54
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	1450822	Tablets			
A.W.C Counter :	1441949	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	260 (0.0%)	Tablets
GOOD :	1441636 (100.0%)	Tablets			