

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	15 Hour 46 Min 10 Sec
Total Counter :	2701350	Total Running Time :	1829 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	37	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.23	kN	No		
HEP :	25.0 %	32.91	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.86	kN	Yes 15	Times	
Ref :		26.33	kN			
LCP :	2.0 %	25.80	kN	Yes 15	Times	
LEP :	25.0 %	19.75	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.32	kN	Punch NO.;	25
SD :	3.90	%	Max :	1.57	kN	Punch NO.;	26
Mean Main Pressure :	26.27	kN	Min :	24.39	kN	Punch NO.;	8
SD :	3.60	%	Max :	28.49	kN	Punch NO.;	26
Filling Depth :	Increase ; 52	Times	Decrease ; 86	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	1.05	mm
Filling Depth :	5.37	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	13
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	29
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	58

Tablet Data (N/A)

Total Counter :	2701350	Tablets			
A.W.C Counter :	2690504	Tablets			
HEP :	72 (0.0%)	Tablets	LEP :	826 (0.0%)	Tablets
GOOD :	2689606 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	15 Hour 46 Min 10 Sec
Total Counter :	2701350	Total Running Time :	1829 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.82	kN	No		
HEP :	25.0 %	35.40	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	28.89	kN	Yes	15	Times
Ref :		28.32	kN			
LCP :	2.0 %	27.75	kN	Yes	15	Times
LEP :	25.0 %	21.24	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	19.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.48	kN	Min :	1.37	kN	Punch NO.;	60
SD :	3.70	%	Max :	1.62	kN	Punch NO.;	23
Mean Main Pressure :	28.48	kN	Min :	26.55	kN	Punch NO.;	63
SD :	3.60	%	Max :	31.05	kN	Punch NO.;	50
Filling Depth :	Increase ;	98	Times	Decrease ;	95	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.62	mm	Main Thickness ;	1.12	mm
Filling Depth :	4.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.17	kN	Max Punch ;	50
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.12	kN	Max Punch ;	29
Ejection Force :	Average ;	0.01	kN		
	Max ;	0.03	kN	Max Punch ;	58

Tablet Data (N/A)

Total Counter :	2701350	Tablets			
A.W.C Counter :	2690504	Tablets			
HEP :	72 (0.0%)	Tablets	LEP :	826 (0.0%)	Tablets
GOOD :	2689606 (100.0%)	Tablets			