

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	os190259	Batch NO. :	KQM2507640
Print Interval :	50000 Tablets	Running Time :	11 Hour 11 Min 02 Sec
Total Counter :	1918470	Total Running Time :	1841 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.60	kN	No		
HEP :	25.0 %	34.23	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.93	kN	Yes 15	Times	
Ref :		27.38	kN			
LCP :	2.0 %	26.83	kN	Yes 15	Times	
LEP :	25.0 %	20.54	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.17	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.30	kN	Punch NO.;	8
SD :	4.30	%	Max :	1.63	kN	Punch NO.;	19
Mean Main Pressure :	27.85	kN	Min :	24.93	kN	Punch NO.;	8
SD :	4.20	%	Max :	30.75	kN	Punch NO.;	19
Filling Depth :	Increase ;	384	Times	Decrease ;	391	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.52	mm	Main Thickness ;	1.02	mm
Filling Depth :	5.35	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	49
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	56
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	1918470	Tablets			
A.W.C Counter :	1911126	Tablets			
HEP :	105 (0.0%)	Tablets	LEP :	537 (0.0%)	Tablets
GOOD :	1910484 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	os190259	Batch NO. :	KQM2507640
Print Interval :	50000 Tablets	Running Time :	11 Hour 11 Min 02 Sec
Total Counter :	1918470	Total Running Time :	1841 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	38.74	kN	No		
HEP :	25.0 %	37.25	kN	Yes	10	Rotations
HCP :	2.0 %	30.39	kN	Yes	15	Times
Ref :		29.80	kN			
LCP :	2.0 %	29.20	kN	Yes	15	Times
LEP :	25.0 %	22.35	kN	Yes	10	Rotations
LSP :	30.0 %	20.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.42	kN	Min :	1.30	kN	Punch NO.;	38
SD :	4.30	%	Max :	1.63	kN	Punch NO.;	43
Mean Main Pressure :	29.74	kN	Min :	27.31	kN	Punch NO.;	63
SD :	3.90	%	Max :	33.79	kN	Punch NO.;	43
Filling Depth :	Increase ;	226	Times	Decrease ;	234	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.59	mm	Main Thickness ;	1.09	mm
Filling Depth :	4.59	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	49
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	44
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	1918470	Tablets			
A.W.C Counter :	1911126	Tablets			
HEP :	105 (0.0%)	Tablets	LEP :	537 (0.0%)	Tablets
GOOD :	1910484 (100.0%)	Tablets			