

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	pb97604	Batch NO. :	KQM2507740
Print Interval :	50000 Tablets	Running Time :	06 Hour 42 Min 14 Sec
Total Counter :	1150638	Total Running Time :	1852 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.20	kN	No		
HEP :	25.0 %	30.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	24.48	kN	Yes 15	Times	
Ref :		24.00	kN			
LCP :	2.0 %	23.52	kN	Yes 15	Times	
LEP :	25.0 %	18.00	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.38	kN	Min :	1.28	kN	Punch NO.;	21
SD :	3.70	%	Max :	1.51	kN	Punch NO.;	43
Mean Main Pressure :	24.18	kN	Min :	21.96	kN	Punch NO.;	48
SD :	3.90	%	Max :	26.90	kN	Punch NO.;	43
Filling Depth :	Increase ; 672	Times	Decrease ;	669	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.61	mm	Main Thickness ;	1.11	mm
Filling Depth :	5.13	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.814	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	16
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	44
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	58

Tablet Data (N/A)

Total Counter :	1150638	Tablets			
A.W.C Counter :	1143481	Tablets			
HEP :	54 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1143427 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : pb97604 Print Interval : 50000 Tablets Total Counter : 1150638 Station : Station 2	Product Name : PANTO40mgSTKQ1B00 Batch NO. : KQM2507740 Running Time : 06 Hour 42 Min 14 Sec Total Running Time : 1852 Hour 52 Min
---	---

Setting Value

Feeder :	Auto ;	28	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.21	kN	No		
HEP :	25.0 %	34.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.41	kN	Yes 15	Times	
Ref :		27.85	kN			
LCP :	2.0 %	27.29	kN	Yes 15	Times	
LEP :	25.0 %	20.89	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.50	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.28	kN	Min :	1.15	kN	Punch NO.;	8
		4.90	%	Max :	1.50	kN	Punch NO.;	17
Mean Main Pressure :		27.76	kN	Min :	25.41	kN	Punch NO.;	5
	SD :	4.30	%	Max :	31.42	kN	Punch NO.;	17
Filling Depth :	Increase ;	357	Times	Decrease ;	359	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.61	mm	Main Thickness ;	1.11	mm
Filling Depth :	4.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.814	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.18	kN	Max Punch ;	11
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	44
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	58

Tablet Data (N/A)

Total Counter :	1150638	Tablets			
A.W.C Counter :	1143546	Tablets			
HEP :	54 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1143492 (100.0%)	Tablets			