

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507740
Print Interval :	50000 Tablets	Running Time :	12 Hour 32 Min 02 Sec
Total Counter :	2151058	Total Running Time :	1858 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.84	kN	No		
HEP :	25.0 %	30.62	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	24.98	kN	Yes 15	Times	
Ref :		24.49	kN			
LCP :	2.0 %	24.00	kN	Yes 15	Times	
LEP :	25.0 %	18.37	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.15	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.40	kN	Min :	1.25	kN	Punch NO.;	34
SD :	4.00	%	Max :	1.58	kN	Punch NO.;	43
Mean Main Pressure :	24.83	kN	Min :	22.36	kN	Punch NO.;	34
SD :	4.20	%	Max :	27.70	kN	Punch NO.;	43
Filling Depth :	Increase ; 711	Times	Decrease ;	698	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.61	mm	Main Thickness ;	1.11	mm
Filling Depth :	5.18	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	75	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.18	kN	Max Punch ;	13
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	44
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	2151058	Tablets			
A.W.C Counter :	2143040	Tablets			
HEP :	58 (0.0%)	Tablets	LEP :	258 (0.0%)	Tablets
GOOD :	2142724 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507740
Print Interval :	50000 Tablets	Running Time :	12 Hour 32 Min 02 Sec
Total Counter :	2151058	Total Running Time :	1858 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.46	kN	No		
HEP :	25.0 %	35.06	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.61	kN	Yes 15	Times	
Ref :		28.05	kN			
LCP :	2.0 %	27.49	kN	Yes 15	Times	
LEP :	25.0 %	21.03	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.63	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.26	kN	Min :	1.15	kN	Punch NO.;	64
SD :	4.30	%	Max :	1.39	kN	Punch NO.;	49
Mean Main Pressure :	27.88	kN	Min :	25.41	kN	Punch NO.;	63
SD :	3.90	%	Max :	30.62	kN	Punch NO.;	35
Filling Depth :	Increase ; 397	Times	Decrease ;	397	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.61	mm	Main Thickness ;	1.11	mm
Filling Depth :	4.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	75	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.17	kN	Max Punch ;	58
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	44
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	2151058	Tablets			
A.W.C Counter :	2143105	Tablets			
HEP :	58 (0.0%)	Tablets	LEP :	258 (0.0%)	Tablets
GOOD :	2142789 (100.0%)	Tablets			