

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	05 Hour 15 Min 24 Sec
Total Counter :	900476	Total Running Time :	1867 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.52	kN	No		
HEP :	25.0 %	31.27	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.52	kN	Yes 15	Times	
Ref :		25.02	kN			
LCP :	2.0 %	24.52	kN	Yes 15	Times	
LEP :	25.0 %	18.76	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.51	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.97	kN	Min :	0.94	kN	Punch NO.;	58
SD :	1.80	%	Max :	1.01	kN	Punch NO.;	1
Mean Main Pressure :	25.22	kN	Min :	23.35	kN	Punch NO.;	47
SD :	3.60	%	Max :	27.12	kN	Punch NO.;	57
Filling Depth :	Increase ;	215	Times	Decrease ;	243	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.60	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	43
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	900476	Tablets			
A.W.C Counter :	888626	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	261 (0.0%)	Tablets
GOOD :	888364 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	05 Hour 15 Min 24 Sec
Total Counter :	900476	Total Running Time :	1867 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.67	kN	No		
HEP :	25.0 %	30.45	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	24.85	kN	Yes	15	Times
Ref :		24.36	kN			
LCP :	2.0 %	23.87	kN	Yes	15	Times
LEP :	25.0 %	18.27	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.05	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.99	kN	Min :	0.96	kN	Punch NO.;	63
SD :	1.90	%	Max :	1.06	kN	Punch NO.;	48
Mean Main Pressure :	24.74	kN	Min :	22.91	kN	Punch NO.;	39
SD :	3.50	%	Max :	26.66	kN	Punch NO.;	48
Filling Depth :	Increase ;	20	Times	Decrease ;	20	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.32	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	43
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	900476	Tablets			
A.W.C Counter :	888626	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	261 (0.0%)	Tablets
GOOD :	888364 (100.0%)	Tablets			