

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	pb97604	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	11 Hour 18 Min 01 Sec
Total Counter :	1938860	Total Running Time :	1873 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	36	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.25	kN	No		
HEP :	25.0 %	33.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.65	kN	Yes 15	Times	
Ref :		27.11	kN			
LCP :	2.0 %	26.57	kN	Yes 15	Times	
LEP :	25.0 %	20.33	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.98	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.04	kN	Min :	0.98	kN	Punch NO.;	6
SD :	3.00	%	Max :	1.13	kN	Punch NO.;	46
Mean Main Pressure :	27.38	kN	Min :	25.17	kN	Punch NO.;	6
SD :	3.90	%	Max :	29.84	kN	Punch NO.;	46
Filling Depth :	Increase ; 96	Times	Decrease ;	112	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.85	mm	Pre Thickness ;	1.86	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.74	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	21
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	1938860	Tablets			
A.W.C Counter :	1926391	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	517 (0.0%)	Tablets
GOOD :	1925872 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	pb97604	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	11 Hour 18 Min 01 Sec
Total Counter :	1938860	Total Running Time :	1873 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.72	kN	No		
HEP :	25.0 %	32.42	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.45	kN	Yes 15	Times	
Ref :		25.94	kN			
LCP :	2.0 %	25.42	kN	Yes 15	Times	
LEP :	25.0 %	19.45	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.92	kN	Punch NO.;	23
SD :	2.60	%	Max :	1.05	kN	Punch NO.;	46
Mean Main Pressure :	26.16	kN	Min :	24.37	kN	Punch NO.;	23
SD :	3.10	%	Max :	27.81	kN	Punch NO.;	54
Filling Depth :	Increase ; 20	Times	Decrease ; 25	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.85	mm	Pre Thickness ;	1.86	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	21
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	1938860	Tablets			
A.W.C Counter :	1926456	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	517 (0.0%)	Tablets
GOOD :	1925937 (100.0%)	Tablets			