

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	sj97904	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	07 Hour 52 Min 16 Sec
Total Counter :	1250624	Total Running Time :	1886 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.97	kN	No		
HEP :	25.0 %	19.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.67	kN	Yes 15	Times	
Ref :		15.36	kN			
LCP :	2.0 %	15.06	kN	Yes 15	Times	
LEP :	25.0 %	11.52	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.75	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.36	kN	Min :	1.29	kN	Punch NO.;	24
SD :	1.80	%	Max :	1.41	kN	Punch NO.;	22
Mean Main Pressure :	15.40	kN	Min :	14.69	kN	Punch NO.;	2
SD :	2.10	%	Max :	16.60	kN	Punch NO.;	27
Filling Depth :	Increase ; 56	Times	Decrease ;	71	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.09	kN	Max Punch ;	50
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.31	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1250624	Tablets			
A.W.C Counter :	1238289	Tablets			
HEP :	0 (0%)	Tablets	LEP :	120 (0.0%)	Tablets
GOOD :	1238169 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	sj97904	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	07 Hour 52 Min 16 Sec
Total Counter :	1250624	Total Running Time :	1886 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.38	kN	No		
HEP :	25.0 %	18.63	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.21	kN	Yes 15	Times	
Ref :		14.91	kN			
LCP :	2.0 %	14.61	kN	Yes 15	Times	
LEP :	25.0 %	11.18	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.44	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.29	kN	Min :	1.22	kN	Punch NO.;	38
SD :	2.60	%	Max :	1.38	kN	Punch NO.;	30
Mean Main Pressure :	14.88	kN	Min :	13.80	kN	Punch NO.;	16
SD :	3.00	%	Max :	15.80	kN	Punch NO.;	39
Filling Depth :	Increase ; 43	Times	Decrease ; 57	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.56	mm	Main Thickness ;	3.07	mm
Filling Depth :	7.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.09	kN	Max Punch ;	10
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.31	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1250624	Tablets			
A.W.C Counter :	1238289	Tablets			
HEP :	0 (0%)	Tablets	LEP :	120 (0.0%)	Tablets
GOOD :	1238169 (100.0%)	Tablets			