

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	os190259	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	13 Hour 45 Min 05 Sec
Total Counter :	2186216	Total Running Time :	1891 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.36	kN	No		
HEP :	25.0 %	19.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.97	kN	Yes 15	Times	
Ref :		15.66	kN			
LCP :	2.0 %	15.35	kN	Yes 15	Times	
LEP :	25.0 %	11.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.36	kN	Min :	1.32	kN	Punch NO.;	36
		1.50	%	Max :	1.41	kN	Punch NO.;	34
Mean Main Pressure :		15.46	kN	Min :	14.77	kN	Punch NO.;	42
	SD :	2.10	%	Max :	16.45	kN	Punch NO.;	53
Filling Depth :	Increase ;	22	Times	Decrease ;	35	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.59	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.45	mm	Current Cam :	Cam C	
Main Air pressure :	0.708	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2186216	Tablets			
A.W.C Counter :	2172773	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2172548 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	os190259	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	13 Hour 45 Min 05 Sec
Total Counter :	2186216	Total Running Time :	1891 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.64	kN	No		
HEP :	25.0 %	18.88	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.41	kN	Yes 15	Times	
Ref :		15.10	kN			
LCP :	2.0 %	14.80	kN	Yes 15	Times	
LEP :	25.0 %	11.33	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.31	kN	Min :	1.22	kN	Punch NO.;	24
SD :	2.90	%	Max :	1.39	kN	Punch NO.;	25
Mean Main Pressure :	15.12	kN	Min :	14.46	kN	Punch NO.;	44
SD :	2.70	%	Max :	16.19	kN	Punch NO.;	10
Filling Depth :	Increase ; 19	Times	Decrease ; 18	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.55	mm	Main Thickness ;	3.06	mm
Filling Depth :	7.43	mm	Current Cam :	Cam C	
Main Air pressure :	0.708	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2186216	Tablets			
A.W.C Counter :	2172773	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2172548 (100.0%)	Tablets			