

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	os190259	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	16 Hour 15 Min 59 Sec
Total Counter :	2586432	Total Running Time :	1894 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.27	kN	No		
HEP :	25.0 %	19.49	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.90	kN	Yes 15	Times	
Ref :		15.59	kN			
LCP :	2.0 %	15.28	kN	Yes 15	Times	
LEP :	25.0 %	11.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.33	kN	Min :	1.28	kN	Punch NO.;	9
		1.90	%	Max :	1.37	kN	Punch NO.;	24
Mean Main Pressure :		15.44	kN	Min :	14.82	kN	Punch NO.;	31
	SD :	2.00	%	Max :	16.10	kN	Punch NO.;	27
Filling Depth :	Increase ;	34	Times	Decrease ;	48	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.59	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	36
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2586432	Tablets			
A.W.C Counter :	2572495	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2572270 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	os190259	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	16 Hour 15 Min 59 Sec
Total Counter :	2586432	Total Running Time :	1894 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.32	kN	No		
HEP :	25.0 %	18.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.16	kN	Yes 15	Times	
Ref :		14.86	kN			
LCP :	2.0 %	14.56	kN	Yes 15	Times	
LEP :	25.0 %	11.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.40	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.59	kN	Min :	1.44	kN	Punch NO.;	32
		3.80	%	Max :	1.74	kN	Punch NO.;	25
Mean Main Pressure :		14.96	kN	Min :	13.99	kN	Punch NO.;	31
	SD :	3.10	%	Max :	16.22	kN	Punch NO.;	39
Filling Depth :	Increase ;	32	Times	Decrease ;	31	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.43	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	36
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	31
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2586432	Tablets			
A.W.C Counter :	2572495	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2572270 (100.0%)	Tablets			