

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	os190259	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	16 Hour 53 Min 43 Sec
Total Counter :	2686500	Total Running Time :	1895 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.27	kN	No		
HEP :	25.0 %	19.49	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.90	kN	Yes 15	Times	
Ref :		15.59	kN			
LCP :	2.0 %	15.28	kN	Yes 15	Times	
LEP :	25.0 %	11.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.35	kN	Min :	1.28	kN	Punch NO.;	14
SD :	1.90	%	Max :	1.42	kN	Punch NO.;	43
Mean Main Pressure :	15.69	kN	Min :	15.07	kN	Punch NO.;	30
SD :	2.20	%	Max :	16.61	kN	Punch NO.;	9
Filling Depth :	Increase ; 34	Times	Decrease ; 48	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.59	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	34
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.24	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2686500	Tablets			
A.W.C Counter :	2672612	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2672387 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	os190259	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	16 Hour 53 Min 43 Sec
Total Counter :	2686500	Total Running Time :	1895 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.33	kN	No		
HEP :	25.0 %	18.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.17	kN	Yes 15	Times	
Ref :		14.87	kN			
LCP :	2.0 %	14.57	kN	Yes 15	Times	
LEP :	25.0 %	11.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.59	kN	Min :	1.47	kN	Punch NO.;	18
		3.50	%	Max :	1.70	kN	Punch NO.;	45
Mean Main Pressure :		14.83	kN	Min :	13.84	kN	Punch NO.;	41
	SD :	3.10	%	Max :	15.78	kN	Punch NO.;	53
Filling Depth :	Increase ;	38	Times	Decrease ;	37	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.24	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2686500	Tablets			
A.W.C Counter :	2672612	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2672387 (100.0%)	Tablets			