

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET500MGSTMR7A00      |
| User ID :        | rp98927       | Batch NO. :          | MRM2502250            |
| Print Interval : | 50000 Tablets | Running Time :       | 18 Hour 13 Min 57 Sec |
| Total Counter :  | 2901342       | Total Running Time : | 1924 Hour 44 Min      |
| Station :        | Station 1     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 89       | %       | Manual ;           | 30           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 4500000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80       | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 30.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 19.80    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 19.04    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 15.54    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 15.23    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 14.93    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 11.43    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 10.66    | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 30.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | None        |          |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.12       | kN  | Min : | 1.95       | kN  | Punch NO.; | 9  |
| SD :                 | 3.40       | %   | Max : | 2.26       | kN  | Punch NO.; | 43 |
| Mean Main Pressure : | 15.34      | kN  | Min : | 14.69      | kN  | Punch NO.; | 42 |
| SD :                 | 2.10       | %   | Max : | 15.93      | kN  | Punch NO.; | 1  |
| Filling Depth :      | Increase ; | 226 | Times | Decrease ; | 207 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25      | RPM | Capacity :       | 159000   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 22       | RPM          |
| Pre Upper Punch Position ;    | 2.49    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.58    | mm  | Pre Thickness ;  | 3.09     | mm           |
| Main Upper Punch Position ;   | 2.49    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.58    | mm  | Main Thickness ; | 3.09     | mm           |
| Filling Depth :               | 7.42    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.794   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 67      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 4       | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 46 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.20 | kN | Max Punch ; | 20 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 2901342             | Tablets |       |            |         |
| A.W.C Counter : | 2895153             | Tablets |       |            |         |
| HEP :           | 3 (0.0%)            | Tablets | LEP : | 298 (0.0%) | Tablets |
| GOOD :          | 2894852<br>(100.0%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                       |
|------------------|---------------|----------------------|-----------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET500MGSTMR7A00      |
| User ID :        | rp98927       | Batch NO. :          | MRM2502250            |
| Print Interval : | 50000 Tablets | Running Time :       | 18 Hour 13 Min 57 Sec |
| Total Counter :  | 2901342       | Total Running Time : | 1924 Hour 44 Min      |
| Station :        | Station 2     |                      |                       |

### Setting Value

|                                    |             |          |         |                    |              |           |
|------------------------------------|-------------|----------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ;      | 89       | %       | Manual ;           | 30           | RPM       |
| Filling Cam :                      |             | Cam C    |         | Cam Range :        | Min :        | 6.50 mm   |
|                                    |             | 8.5-14mm |         |                    | Max :        | 12.00 mm  |
| Target Quantity :                  |             | 4500000  | Tablets |                    |              |           |
| Air Pressure Low Limit :           |             | 0.400    | MPa     |                    |              |           |
| Oil Lubrication :                  |             |          |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |             | 80       | Min     | Supply Time ;      | 0.5          | Sec       |
| Lower Punch Interval Time(S2) ;    |             | 20       | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |             | 30.0     | Sec     |                    |              |           |
| Initial Reject Time :              |             | 2        | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |             | 1.00     | kN      |                    |              |           |
| Ejecting Force High Limit :        |             | 4.00     | kN      |                    |              |           |
|                                    |             |          |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 %      | 19.33    | kN      | No                 |              |           |
| HEP :                              | 25.0 %      | 18.59    | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %       | 15.17    | kN      | Yes 15             | Times        |           |
| Ref :                              |             | 14.87    | kN      |                    |              |           |
| LCP :                              | 2.0 %       | 14.57    | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 %      | 11.15    | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 %      | 10.41    | kN      | No                 |              |           |
| SD limit :                         | 35.0 %      |          |         | Yes                |              |           |
| Pre HSP                            |             | 30.00    | kN      | Yes                |              |           |
| Mean Calculation range :           | 2 Rotations |          |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N           |          |         |                    |              |           |

### Pressure Data

|                      |                |       |            |       |       |            |    |
|----------------------|----------------|-------|------------|-------|-------|------------|----|
| Mean Pre Pressure :  | 1.57           | kN    | Min :      | 1.43  | kN    | Punch NO.; | 24 |
| SD :                 | 3.30           | %     | Max :      | 1.68  | kN    | Punch NO.; | 8  |
| Mean Main Pressure : | 14.75          | kN    | Min :      | 13.82 | kN    | Punch NO.; | 45 |
| SD :                 | 2.80           | %     | Max :      | 15.64 | kN    | Punch NO.; | 39 |
| Filling Depth :      | Increase ; 314 | Times | Decrease ; | 294   | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 25     | RPM | Capacity :       | 159000   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 22       | RPM          |
| Pre Upper Punch Position ;    | 2.49   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.80   | mm  | Pre Thickness ;  | 3.31     | mm           |
| Main Upper Punch Position ;   | 2.49   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.60   | mm  | Main Thickness ; | 3.11     | mm           |
| Filling Depth :               | 7.37   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.794  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 67     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 4      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.12 | kN | Max Punch ; | 46 |
| Lower Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.21 | kN | Max Punch ; | 20 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                     |         |       |            |         |
|-----------------|---------------------|---------|-------|------------|---------|
| Total Counter : | 2901342             | Tablets |       |            |         |
| A.W.C Counter : | 2895153             | Tablets |       |            |         |
| HEP :           | 3 (0.0%)            | Tablets | LEP : | 298 (0.0%) | Tablets |
| GOOD :          | 2894852<br>(100.0%) | Tablets |       |            |         |