

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	kp99540	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	00 Hour 49 Min 21 Sec
Total Counter :	200142	Total Running Time :	1935 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	15.32	kN	No		
HEP :	20.0 %	14.71	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.50	kN	Yes	15	Times
Ref :		12.26	kN			
LCP :	2.0 %	12.01	kN	Yes	15	Times
LEP :	20.0 %	9.80	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	9.19	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.14	kN	Min :	1.93	kN	Punch NO.;	64
SD :	2.40	%	Max :	2.23	kN	Punch NO.;	5
Mean Main Pressure :	12.17	kN	Min :	9.97	kN	Punch NO.;	64
SD :	4.60	%	Max :	13.46	kN	Punch NO.;	5
Filling Depth :	Increase ;	0	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.00	mm
Filling Depth :	5.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	66	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.62	kN	Max Punch ;	5
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	36
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200142	Tablets			
A.W.C Counter :	201429	Tablets			
HEP :	136 (0.1%)	Tablets	LEP :	219 (0.1%)	Tablets
GOOD :	201074 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	kp99540	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	00 Hour 49 Min 21 Sec
Total Counter :	200142	Total Running Time :	1935 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	36	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	14.25	kN	No		
HEP :	20.0 %	13.68	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.62	kN	Yes 15	Times	
Ref :		11.40	kN			
LCP :	2.0 %	11.17	kN	Yes 15	Times	
LEP :	20.0 %	9.12	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	8.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.40	kN	Min :	2.11	kN	Punch NO.;	8
SD :	3.00	%	Max :	2.55	kN	Punch NO.;	77
Mean Main Pressure :	11.56	kN	Min :	9.61	kN	Punch NO.;	8
SD :	4.10	%	Max :	12.60	kN	Punch NO.;	77
Filling Depth :	Increase ;	5	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	2.30	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.16	mm	Main Thickness ;	2.16	mm
Filling Depth :	5.51	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	66	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.42	kN		
	Max ;	0.64	kN	Max Punch ;	14
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	36
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200142	Tablets			
A.W.C Counter :	201429	Tablets			
HEP :	136 (0.1%)	Tablets	LEP :	219 (0.1%)	Tablets
GOOD :	201074 (99.8%)	Tablets			