

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	kp99540	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	02 Hour 13 Min 55 Sec
Total Counter :	550448	Total Running Time :	1936 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	15.32	kN	No		
HEP :	20.0 %	14.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.50	kN	Yes 15	Times	
Ref :		12.26	kN			
LCP :	2.0 %	12.01	kN	Yes 15	Times	
LEP :	20.0 %	9.80	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	9.19	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.96	kN	Min :	1.77	kN	Punch NO.;	64
SD :	2.20	%	Max :	2.03	kN	Punch NO.;	46
Mean Main Pressure :	12.37	kN	Min :	10.34	kN	Punch NO.;	64
SD :	4.10	%	Max :	13.50	kN	Punch NO.;	57
Filling Depth :	Increase ; 8	Times	Decrease ; 18	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.00	mm	Main Thickness ;	2.00	mm
Filling Depth :	5.70	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550448	Tablets			
A.W.C Counter :	562408	Tablets			
HEP :	140 (0.0%)	Tablets	LEP :	715 (0.1%)	Tablets
GOOD :	561553 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	kp99540	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	02 Hour 13 Min 55 Sec
Total Counter :	550448	Total Running Time :	1936 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	36	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	14.25	kN	No		
HEP :	20.0 %	13.68	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.62	kN	Yes 15	Times	
Ref :		11.40	kN			
LCP :	2.0 %	11.17	kN	Yes 15	Times	
LEP :	20.0 %	9.12	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	8.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.25	kN	Min :	2.04	kN	Punch NO.;	65
		2.60	%	Max :	2.37	kN	Punch NO.;	4
Mean Main Pressure :	SD :	11.61	kN	Min :	10.34	kN	Punch NO.;	65
		3.50	%	Max :	12.45	kN	Punch NO.;	25
Filling Depth :	Increase ;	13	Times	Decrease ;	24	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.30	mm	Pre Thickness ;	2.30	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.16	mm	Main Thickness ;	2.16	mm
Filling Depth :	5.39	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	31
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550448	Tablets			
A.W.C Counter :	562408	Tablets			
HEP :	140 (0.0%)	Tablets	LEP :	715 (0.1%)	Tablets
GOOD :	561553 (99.8%)	Tablets			