

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	06 Hour 27 Min 51 Sec
Total Counter :	1601222	Total Running Time :	1941 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	15.35	kN	No		
HEP :	20.0 %	14.74	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	12.53	kN	Yes 15	Times	
Ref :		12.28	kN			
LCP :	2.0 %	12.04	kN	Yes 15	Times	
LEP :	20.0 %	9.83	kN	Yes 10	Rotations 20	Tablets
LSP :	25.0 %	9.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.97	kN	Min :	1.74	kN	Punch NO.;	8
SD :	2.10	%	Max :	2.04	kN	Punch NO.;	34
Mean Main Pressure :	12.40	kN	Min :	9.66	kN	Punch NO.;	8
SD :	4.20	%	Max :	13.23	kN	Punch NO.;	73
Filling Depth :	Increase ; 38	Times	Decrease ;	73	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.10	mm	Main Thickness ;	2.10	mm
Filling Depth :	5.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.728	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	18
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1601222	Tablets			
A.W.C Counter :	1587528	Tablets			
HEP :	176 (0.0%)	Tablets	LEP :	2515 (0.2%)	Tablets
GOOD :	1584837 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pr190041	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	06 Hour 27 Min 51 Sec
Total Counter :	1601222	Total Running Time :	1941 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	25.0 %	14.50	kN	No		
HEP :	20.0 %	13.92	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	11.84	kN	Yes 15	Times	
Ref :		11.60	kN			
LCP :	2.0 %	11.37	kN	Yes 15	Times	
LEP :	20.0 %	9.28	kN	Yes 10	Rotations 20	Tablets
LSP :	25.0 %	8.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.97	kN	Min :	1.84	kN	Punch NO.;	64
SD :	2.50	%	Max :	2.09	kN	Punch NO.;	32
Mean Main Pressure :	11.62	kN	Min :	10.62	kN	Punch NO.;	64
SD :	3.20	%	Max :	12.52	kN	Punch NO.;	57
Filling Depth :	Increase ;	33	Times	Decrease ;	70	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.22	mm
Filling Depth :	5.57	mm	Current Cam :	Cam B	
Main Air pressure :	0.728	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	18
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1601222	Tablets			
A.W.C Counter :	1587528	Tablets			
HEP :	176 (0.0%)	Tablets	LEP :	2515 (0.2%)	Tablets
GOOD :	1584837 (99.8%)	Tablets			