

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	09 Hour 10 Min 48 Sec
Total Counter :	2301722	Total Running Time :	1943 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.20	kN	No		
HEP :	25.0 %	15.58	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.65	kN	Yes 15	Times	
Ref :		12.46	kN			
LCP :	1.5 %	12.28	kN	Yes 15	Times	
LEP :	25.0 %	9.35	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.97	kN	Min :	1.72	kN	Punch NO.;	8
SD :	2.30	%	Max :	2.05	kN	Punch NO.;	50
Mean Main Pressure :	12.38	kN	Min :	9.49	kN	Punch NO.;	8
SD :	4.50	%	Max :	13.42	kN	Punch NO.;	1
Filling Depth :	Increase ;	64	Times	Decrease ;	100	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.11	mm	Main Thickness ;	2.11	mm
Filling Depth :	5.81	mm	Current Cam :	Cam B	
Main Air pressure :	0.763	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	67	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	8
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2301722	Tablets			
A.W.C Counter :	2282511	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	6471 (0.3%)	Tablets
GOOD :	2275862 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	09 Hour 10 Min 48 Sec
Total Counter :	2301722	Total Running Time :	1943 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.15	kN	No		
HEP :	25.0 %	14.56	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	11.83	kN	Yes 15	Times	
Ref :		11.65	kN			
LCP :	1.5 %	11.48	kN	Yes 15	Times	
LEP :	25.0 %	8.74	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.55	kN	Punch NO.;	8
SD :	3.50	%	Max :	2.07	kN	Punch NO.;	30
Mean Main Pressure :	11.48	kN	Min :	7.68	kN	Punch NO.;	8
SD :	5.50	%	Max :	12.29	kN	Punch NO.;	30
Filling Depth :	Increase ;	81	Times	Decrease ;	128	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.22	mm
Filling Depth :	5.57	mm	Current Cam :	Cam B	
Main Air pressure :	0.763	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	67	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	8
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2301722	Tablets			
A.W.C Counter :	2282511	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	6471 (0.3%)	Tablets
GOOD :	2275862 (99.7%)	Tablets			