

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	os190259	Batch NO. :	SHM2502550
Print Interval :	50000 Tablets	Running Time :	02 Hour 42 Min 19 Sec
Total Counter :	700566	Total Running Time :	1983 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.88	kN	No		
HEP :	25.0 %	15.27	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.40	kN	Yes 15	Times	
Ref :		12.22	kN			
LCP :	1.5 %	12.03	kN	Yes 15	Times	
LEP :	25.0 %	9.16	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.86	kN	Min :	1.77	kN	Punch NO.;	3
SD :	2.10	%	Max :	1.95	kN	Punch NO.;	50
Mean Main Pressure :	12.18	kN	Min :	10.94	kN	Punch NO.;	47
SD :	4.10	%	Max :	13.40	kN	Punch NO.;	72
Filling Depth :	Increase ;	498	Times	Decrease ;	598	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	5.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.17	kN	Max Punch ;	65
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	59
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700566	Tablets			
A.W.C Counter :	696196	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	696189 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	os190259	Batch NO. :	SHM2502550
Print Interval :	50000 Tablets	Running Time :	02 Hour 42 Min 19 Sec
Total Counter :	700566	Total Running Time :	1983 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.89	kN	No		
HEP :	25.0 %	14.31	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	11.62	kN	Yes 15	Times	
Ref :		11.45	kN			
LCP :	1.5 %	11.28	kN	Yes 15	Times	
LEP :	25.0 %	8.59	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.81	kN	Min :	1.70	kN	Punch NO.;	61
SD :	2.40	%	Max :	1.95	kN	Punch NO.;	8
Mean Main Pressure :	11.41	kN	Min :	10.23	kN	Punch NO.;	61
SD :	4.60	%	Max :	12.98	kN	Punch NO.;	8
Filling Depth :	Increase ;	465	Times	Decrease ;	537	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.65	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.17	kN	Max Punch ;	65
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700566	Tablets			
A.W.C Counter :	696196	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	696189 (100.0%)	Tablets			