

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502550
Print Interval :	50000 Tablets	Running Time :	10 Hour 32 Min 02 Sec
Total Counter :	2727746	Total Running Time :	1991 Hour 10 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.64	kN	No		
HEP :	25.0 %	16.00	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.00	kN	Yes 15	Times	
Ref :		12.80	kN			
LCP :	1.5 %	12.61	kN	Yes 15	Times	
LEP :	25.0 %	9.60	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.96	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.81	kN	Punch NO.;	20
SD :	1.80	%	Max :	1.99	kN	Punch NO.;	38
Mean Main Pressure :	12.81	kN	Min :	11.56	kN	Punch NO.;	20
SD :	3.90	%	Max :	14.06	kN	Punch NO.;	38
Filling Depth :	Increase ; 124	Times	Decrease ;	98	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.59	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	6.01	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.26	kN	Max Punch ;	70
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2727746	Tablets			
A.W.C Counter :	2721192	Tablets			
HEP :	7 (0.0%)	Tablets	LEP :	910 (0.0%)	Tablets
GOOD :	2720275 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502550
Print Interval :	50000 Tablets	Running Time :	10 Hour 32 Min 02 Sec
Total Counter :	2727746	Total Running Time :	1991 Hour 10 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.48	kN	No		
HEP :	25.0 %	15.85	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.87	kN	Yes 15	Times	
Ref :		12.68	kN			
LCP :	1.5 %	12.49	kN	Yes 15	Times	
LEP :	25.0 %	9.51	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.86	kN	Min :	1.79	kN	Punch NO.;	4
		1.80	%	Max :	1.95	kN	Punch NO.;	76
Mean Main Pressure :		12.84	kN	Min :	12.14	kN	Punch NO.;	64
	SD :	3.30	%	Max :	14.14	kN	Punch NO.;	44
Filling Depth :	Increase ;	22	Times	Decrease ;	30	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.49	mm	Pre Thickness ;	2.49	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	70
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2727746	Tablets			
A.W.C Counter :	2721269	Tablets			
HEP :	7 (0.0%)	Tablets	LEP :	910 (0.0%)	Tablets
GOOD :	2720352 (100.0%)	Tablets			