

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	yu98249	Batch NO. :	SHM2502650
Print Interval :	50000 Tablets	Running Time :	15 Hour 27 Min 22 Sec
Total Counter :	4002762	Total Running Time :	2019 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.30	kN	No		
HEP :	25.0 %	14.71	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	11.95	kN	Yes 15	Times	
Ref :		11.77	kN			
LCP :	1.5 %	11.59	kN	Yes 15	Times	
LEP :	25.0 %	8.83	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.68	kN	Punch NO.;	9
SD :	1.80	%	Max :	1.84	kN	Punch NO.;	27
Mean Main Pressure :	11.68	kN	Min :	10.56	kN	Punch NO.;	59
SD :	4.00	%	Max :	12.90	kN	Punch NO.;	44
Filling Depth :	Increase ;	615	Times	Decrease ;	565	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.59	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.15	mm	Main Thickness ;	2.15	mm
Filling Depth :	5.86	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.794	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.23	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4002762	Tablets			
A.W.C Counter :	3996838	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	3996836 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	yu98249	Batch NO. :	SHM2502650
Print Interval :	50000 Tablets	Running Time :	15 Hour 27 Min 22 Sec
Total Counter :	4002762	Total Running Time :	2019 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.62	kN	No		
HEP :	25.0 %	15.02	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.19	kN	Yes 15	Times	
Ref :		12.01	kN			
LCP :	1.5 %	11.83	kN	Yes 15	Times	
LEP :	25.0 %	9.01	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.67	kN	Punch NO.;	68
SD :	2.30	%	Max :	1.88	kN	Punch NO.;	5
Mean Main Pressure :	11.90	kN	Min :	10.65	kN	Punch NO.;	58
SD :	4.20	%	Max :	13.45	kN	Punch NO.;	5
Filling Depth :	Increase ;	288	Times	Decrease ;	314	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.49	mm	Pre Thickness ;	2.49	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.61	mm	Current Cam :	Cam B	
Main Air pressure :	0.794	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4002762	Tablets			
A.W.C Counter :	3996838	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	3996836 (100.0%)	Tablets			