

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	yu98249	Batch NO. :	SHM2502650
Print Interval :	50000 Tablets	Running Time :	17 Hour 11 Min 44 Sec
Total Counter :	4453124	Total Running Time :	2020 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.66	kN	No		
HEP :	25.0 %	15.06	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.23	kN	Yes 15	Times	
Ref :		12.05	kN			
LCP :	1.5 %	11.87	kN	Yes 15	Times	
LEP :	25.0 %	9.03	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.78	kN	Min :	1.70	kN	Punch NO.;	59
		1.60	%	Max :	1.84	kN	Punch NO.;	70
Mean Main Pressure :		12.13	kN	Min :	10.96	kN	Punch NO.;	59
	SD :	3.40	%	Max :	13.16	kN	Punch NO.;	52
Filling Depth :	Increase ;	640	Times	Decrease ;	601	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.59	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.15	mm	Main Thickness ;	2.15	mm
Filling Depth :	5.89	mm	Current Cam :	Cam B	
Main Air pressure :	0.780	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.30	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4453124	Tablets			
A.W.C Counter :	4447211	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	4447209 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	yu98249	Batch NO. :	SHM2502650
Print Interval :	50000 Tablets	Running Time :	17 Hour 11 Min 44 Sec
Total Counter :	4453124	Total Running Time :	2020 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.57	kN	No		
HEP :	25.0 %	15.94	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.94	kN	Yes 15	Times	
Ref :		12.75	kN			
LCP :	1.5 %	12.56	kN	Yes 15	Times	
LEP :	25.0 %	9.56	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.92	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.85	kN	Min :	1.73	kN	Punch NO.;	61
SD :	2.20	%	Max :	1.97	kN	Punch NO.;	5
Mean Main Pressure :	12.86	kN	Min :	11.38	kN	Punch NO.;	61
SD :	3.80	%	Max :	14.56	kN	Punch NO.;	5
Filling Depth :	Increase ;	292	Times	Decrease ;	331	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.49	mm	Pre Thickness ;	2.49	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.780	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.30	kN	Max Punch ;	63
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4453124	Tablets			
A.W.C Counter :	4447211	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	4447209 (100.0%)	Tablets			